



**Arraystorm**<sup>TM</sup>  
Sense the future

# PRICE CATALOG

w.e.f June 2024

WHERE INNOVATION MEETS ILLUMINATION





RR Kabel Ltd is more than a 1.25 Billion conglomerate in the electrical sector with a presence in over 90 countries globally. RR Global which has many brands under its umbrella, has always endeavoured to create products of the higher quality using the latest in innovative technology. Spread across multiple business verticals including Wires & Cables, Switches, Fans, Lighting, Switchgears & Appliances and now has a complete Lighting portfolio through the acquisition of Arraystorm.

We have grown by leaps and bounds since our inception way back in 1986, as a small trading company.

Our international presence in over 90 countries has reinforced the “Make in India” growth story. Our commitment to deliver top notch quality product continues relentlessly. Stringent adherence to the highest safety standards, continuous endeavour to improve efficiencies while maintaining reliability and consistency is our forte.

As a company responsible for our societal commitments, we assiduously work towards various CSR initiatives in areas of skill development, education, and healthcare.

In 2020, Arraystorm brand and its LED Lighting products was added into the portfolio of RR Kabel Limited, a public listed Company and a name admired worldwide in the electrical industry. Arraystorm – is a premium LED lighting brand known for its energy-efficient customised lighting solutions. Arraystorm reinforces RR Kabel's philosophy of offering unique innovative products & solutions and widens the choice for the customer at the premium end.



Arraystorm focuses on the functional & professional LED lighting business. We create energy-efficient lighting products at our state-of-the-art factory in Bengaluru. Our aim is to deliver custom designed, high quality and high value lighting solutions to people and places worldwide.

Our products are insight-driven and specially designed to suit each and every customer. We believe that our strong focus on technology and innovation will make the world a brighter place. To us the future is a challenge, the kind that we are ready to meet head-on, and we progress on a daily basis to become India's most innovative LED lighting application brand.

At Arraystorm, we do not design products, we design outcomes. Our products and solutions are a result of our futuristic thinking so as to create energy efficient and sustainable products. We do not consider the development of new lighting technologies to be our final destination, instead, we believe in focusing on addressing daily lighting problems. This helps us constantly deliver innovative, exciting, and practical solutions, to address our customers' needs.

# OUR VISION

Reinvent LED lighting and deliver the best illumination experience to our customers.





# OUR MISSION

Build world-class, intelligent  
LED lighting products to deliver comfortable and elevated experience in any space:  
delight the customer in every engagement.

## OUR BELIEF

We are driven by one core belief  
that a bunch of ordinary people can solve the most extraordinary challenges. As a  
team, fuelled with sincerity, compassion and aspirations, we want to redefine the  
idea of customer delight.

The idea is to inculcate applications of light that are executed in anticipation of our  
consumer's needs.

Every single day, we will present customers with impeccable, insight-driven  
experiences, guided by innovation led expertise. Arraystorm aspires to be the  
thought leader, with innovation and application at its heart's center. We articulate  
our passion with our designs, quality and by delivering industry's most impeccable  
customer experience.

Our belief is to change the way people perceive light and  
conquer the grey.

# MANUFACTURING





All the products of Arraystorm are manufactured in our state of the art manufacturing facility at Bengaluru, Karnataka.

The manufacturing capability has in house fabrication facility to process any type of aluminium and steel in terms of cutting, bending, post processing like Punching, drilling, tapping, welding operations.

The state of the art Surface Mounted Technology (SMT) Line equipped with automatic machine ensures the LED are mounted and soldered with high precision and quality tested before getting assembled into the luminaires.

A highly flexible assembly line has been designed to ensure fast and precise Assembly and extremely flexible to ensure Project wise manufacturing, packing and dispatches.

All Raw materials and Finished goods are stored in large facilities to enable fast manufacturing of LED Products.

# DESIGN & DEVELOPMENT (R&D)



Our products are of the highest quality thanks to rigorous R&D which each product undergoes before manufacturing.

Arraystorm implements an inclusive design and innovation ecosystem with a separate and dedicated R&D facility at our unit located in Bengaluru.

Here we do research, Design & Develop new products and concepts through our dedicated product design team consisting of Product designers who create new design of Advanced 3D tools and Engineering team who convert these ideas through the cycle of Prototyping, 2D Drawings, designs of Tools and Dies, Pilot production and rigorous testing converting these unique design concepts into Realities.

All the In-house designed products of Arraystorm are “Designed Registered” and unique.

# QUALITY & TESTING FACILITIES & QUALITY COMPLIANCES

Our central quality and test laboratory for Luminaires in our facility at Bengaluru, Karnataka is complete and can perform all test in house as per ISO/IEC 10322. It is capable of performing all tests on our products. In addition, we have well-equipped laboratories for process monitoring, raw material testing and type testing of products.

**We have a full fledged Photometric Lab to be able to create IES files used for designing Lux levels for any facilities where our lighting is installed and guarantee the Lux levels at sites as per design.**

We also have qualified Design application Engineers at our various branches who do the layout design and give this service to our Esteemed Customers.

At RR Kabel Ltd. safety for all is paramount. Therefore, all our products are certified and compliant with the highest safety standards.

Our range of Led Luminaires conform to national and international standards. Nationally we are certified to the various ISI standards

**All Our Products conform to the  
latest ISI, ISO, CE & IEC Standards.**



# INDEX

## INDOOR

1-25

|                   |    |
|-------------------|----|
| GRIDLIGHT         | 1  |
| DOWNLIGHT         | 4  |
| LINEAR CHANNEL    | 8  |
| ARCHITECTURAL     | 18 |
| BATTEN COMMERCIAL | 24 |
| STRIP LIGHT       | 25 |

## RETAIL

26-34

|                           |    |
|---------------------------|----|
| RECESS SPOTLIGHT          | 26 |
| SURFACE SPOTLIGHT         | 28 |
| LOW GLARE LASER SPOTLIGHT | 29 |
| TRACK LIGHT               | 31 |
| MAGNETIC SERIES           | 32 |

## INDUSTRIAL

35-42

|                   |    |
|-------------------|----|
| HIGH BAY          | 35 |
| BATTEN INDUSTRIAL | 41 |
| TRUNK             | 42 |
| WELLGLASS         | 42 |

## OUTDOOR

43-49

|                     |    |
|---------------------|----|
| FLOOD LIGHT         | 43 |
| STREET / ROAD LIGHT | 48 |

## CLEANROOM

50-56

BOCR

50

TOCR

53

## FLAMEPROOF

CLEANROOM

57

WELLGLASS

60

FLOODLIGHT

61

STREET LIGHT

61

REACTOR LIGHT

62

LINEAR LIGHT

62

## LANDSCAPE

63-73

BOLLARD

63

POST TOP

65

BUSH LIGHT

69

WALL LIGHT

70

STEP LIGHT

72

WALL WASHER

73

## LIGHTING CONTROLS

74-78

WIRED SENSORS

74


IOT SENSORS

75



A modern office interior with a white desk, a black office chair, and a laptop. The room has large windows and is decorated with orange geometric overlays. A large orange rectangle in the center contains the word "INDOOR" in white. The floor is light gray, and there are some plants in the background.

# INDOOR



## EPIC 1 GL2102 (SURFACE GRIDLIGHT 1X1)

Arraystorm EPIC 1, High Efficiency 1X1 LED Surface Gridlight, Body made of CRCA and Opal Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver,  
CRI>80, CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog | White color tunable

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| GL2102FFXXN015N000000000 | 15       | 120        | 300   300   50              | 3500      |
| GL2102FFXXN024N000000000 | 24       | 120        | 300   300   50              | 4000      |



## EPIC 1 GL2001 (RECESS GRIDLIGHT 1X1)

Arraystorm EPIC 1, High Efficiency 1X1 LED Recess Gridlight, Body made of CRCA and Opal Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog | White color tunable. For POP | Gypsum ceiling, frame to be ordered separately.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| GL2001RFXXN015N000000000 | 15       | 120        | 293   293   88              | 3750      |
| GL2001RFXXN024N000000000 | 24       | 120        | 293   293   88              | 4250      |



## EPIC 1 GL2002 (RECESS GRIDLIGHT 2X2)

Arraystorm EPIC 1 Recessed High Efficiency 2X2 LED Gridlight, Body made of CRCA and Opal Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K. Driver also available in DALI | Analog | White color tunable. For POP | Gypsum ceiling, frame to be ordered separately.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| GL2002RFXXN028N000000000 | 28       | 120        | 595   595   88              | 5500      |
| GL2002RFXXN035N000000000 | 35       | 120        | 595   595   88              | 5500      |
| GL2002RFXXN042N000000000 | 42       | 120        | 595   595   88              | 6000      |
| GL2002RFXXN070N000000000 | 70       | 120        | 595   595   88              | 7750      |



## GENYSIS M GL2016 (SURFACE GRIDLIGHT 2X2)

Arraystorm Genysis M, High Efficiency 2X2 LED Surface Gridlight, Body made of CRCA and Opal Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog | White color tunable.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| GL2016FFXXN028N000000000 | 28       | 120        | 595   595   65              | 4500      |
| GL2016FFXXN035N000000000 | 35       | 120        | 595   595   65              | 4500      |
| GL2016FFXXN042N000000000 | 42       | 120        | 595   595   65              | 5250      |



## GENYSIS M GL2017 (RECESS GRIDLIGHT 2X2)

Arraystorm Genysis M, High Efficiency 2X2 LED Recessed Gridlight, Body made of CRCA and Opal Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog | White color tunable.  
For POP | Gypsum ceiling, frame to be ordered separately.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| GL2017RFXXN028N000000000 | 28       | 120        | 595   595   65              | 4500      |
| GL2017RFXXN035N000000000 | 35       | 120        | 595   595   65              | 4500      |
| GL2017RFXXN042N000000000 | 42       | 120        | 595   595   65              | 5000      |



## ASTRO GL2011 (RECESS GRIDLIGHT 2X2)

Arraystorm ASTRO Deep Inset, Curved Body, Recessed 2X2 LED Gridlight, Body made of ABS Plastic and Aluminium Gear tray, Opal Diffuser, homogeneous light distribution.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog | White color tunable.  
For POP | Gypsum ceiling, frame to be ordered separately.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| GL2011RFXXN028N000000000 | 28       | 120        | 595   595   88              | 5750      |
| GL2011RFXXN035N000000000 | 35       | 120        | 595   595   88              | 5750      |
| GL2011RFXXN042N000000000 | 42       | 120        | 595   595   88              | 6500      |



## EPIC 1 GL2026 (RECESS GRIDLIGHT 2X2 - CLIP ON TILE)

Arraystorm EPIC 1, High Efficiency 2X2 LED Clip on Metal ceiling, Recessed Gridlight, Body made of CRCA and Opal Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog | White color tunable.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| GL2026COXXN028N000000000 | 28       | 120        | 600   600   65              | 6500      |
| GL2026COXXN035N000000000 | 35       | 120        | 600   600   65              | 6750      |
| GL2026COXXN042N000000000 | 42       | 120        | 600   600   65              | 6750      |



## EPIC 2 GL4002 (RECESS GRIDLIGHT 1X4)

Arraystorm EPIC 2, High Efficiency 1X4 LED Metal ceiling, Recessed Gridlight, Body made of CRCA and Opal Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog | White color tunable.  
For POP | Gypsum ceiling, frame to be ordered separately.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| GL4002RFXXN028N000000000 | 28       | 120        | 1195   295   88             | 6500      |
| GL4002RFXXN035N000000000 | 35       | 120        | 1195   295   88             | 6500      |
| GL4002RFXXN042N000000000 | 42       | 120        | 1195   295   88             | 7250      |



## EPIC 2 GL4003 (SURFACE GRIDLIGHT 1X4)

Arraystorm EPIC 2, High Efficiency 1X4 LED Metal ceiling, Surface Gridlight, Body made of CRCA and Opal Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog | White color tunable.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| GL4003FFXXN028N000000000 | 28       | 120        | 1195   295   88             | 6500      |
| GL4003FFXXN035N000000000 | 35       | 120        | 1195   295   88             | 6500      |
| GL4003FFXXN042N000000000 | 42       | 120        | 1195   295   88             | 7250      |



## EPIC 2 GL2004 (RECESS GRIDLIGHT 2X4)

Arraystorm EPIC 2, High Efficiency 2X4 LED Metal ceiling, Recessed Gridlight, Body made of CRCA and Opal Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog | White color tunable.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| GL2004RFXXN056N000000000 | 56       | 120        | 1195   595   88             | 13250     |
| GL2004RFXXN070N000000000 | 70       | 120        | 1195   595   88             | 13250     |
| GL2004RFXXN084N000000000 | 84       | 120        | 1195   595   88             | 16500     |



## LINEAGE TZ RF GL1458 (RECESSED TECHZONE)

Arraystorm LINEAGE TZ High Efficiency Recessed Techzone LED Grid light, Body made of Aluminium and Opal Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog | White color tunable.  
For POP | Gypsum ceiling, frame to be ordered separately.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| GL1458RFXXN030N4FS000000 | 30       | 120        | 1195   145   58             | 9500      |
| GL1458RFXXN040N8FS000000 | 40       | 120        | 2395   145   58             | 13500     |
| GL1458RFXXN060N8FS000000 | 60       | 120        | 2395   145   58             | 14750     |



## SWANK R DL1003/DL1004 (RECESSED DOWNLIGHT)

Arraystorm SWANK R LED Recessed High Efficiency Round Downlight, Body made of Aluminium and Opal Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog | White color tunable.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>Dia | DIMENSION (mm)<br>Dia   H | MRP (INR) |
|--------------------------|----------|------------|--------------------|---------------------------|-----------|
| DL1003RFXXN007N000000000 | 7        | 120        | 136                | 142   44                  | 1350      |
| DL1003RFXXN010N000000000 | 10       | 120        | 136                | 142   44                  | 1400      |
| DL1003RFXXN015N000000000 | 15       | 120        | 136                | 142   44                  | 1400      |
| DL1004RFXXN018N000000000 | 18       | 120        | 194                | 200   44                  | 2250      |
| DL1004RFXXN024N000000000 | 24       | 120        | 194                | 200   44                  | 2500      |



## SWANK DR DL1012/DL1013/DL1014 (DEEP RECESSED DOWNLIGHT)

Arraystorm SWANK DR LED Deep Recessed High Efficiency Round Downlight, Body made of pressure diecast Aluminium and Opal Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog | White color tunable.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>Dia | DIMENSION (mm)<br>Dia   H | MRP (INR) |
|---------------------------|----------|------------|--------------------|---------------------------|-----------|
| DL1012RFXXN007N0000000000 | 7        | 120        | 110                | 120   50                  | 1500      |
| DL1012RFXXN012N0000000000 | 12       | 120        | 110                | 120   50                  | 1500      |
| DL1013RFXXN015N0000000000 | 15       | 120        | 145                | 155   58                  | 1750      |
| DL1013RFXXN018N0000000000 | 18       | 120        | 145                | 155   58                  | 2250      |
| DL1014RFXXN024N0000000000 | 24       | 120        | 165                | 175   54                  | 2500      |



## SWANK DRLR DL1017/DL1018/DL1019 (DEEP RECESSED LOW GLARE DOWNLIGHT)

Arraystorm SWANK DRLR Deep Recessed Low Glare High Efficiency Round Downlight, Body made of pressure diecast Aluminium and Opal Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog | White color tunable.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>Dia | DIMENSION (mm)<br>Dia   H | MRP (INR) |
|---------------------------|----------|------------|--------------------|---------------------------|-----------|
| DL1017RFXXN007N0000000000 | 7        | 120        | 130                | 135   62                  | 1750      |
| DL1017RFXXN012N0000000000 | 12       | 120        | 130                | 135   62                  | 2000      |
| DL1017RFXXN015N0000000000 | 15       | 120        | 130                | 135   62                  | 2000      |
| DL1017RFXXN015N0000000054 | 15       | 120        | 130                | 135   62                  | 2500      |
| DL1018RFXXN018N0000000000 | 18       | 120        | 170                | 178   62                  | 2500      |
| DL1018RFXXN024N0000000000 | 24       | 120        | 170                | 178   62                  | 2750      |
| DL1019RFXXN030N0000000000 | 30       | 120        | 205                | 214   62                  | 3500      |



## SWANK DR SQUARE DL1005/DL1006 (RECESSED DOWNLIGHT)

Arraystorm SWANK DR SQ LED Deep Recessed High Efficiency Square Downlight, Body made of pressure diecast Aluminium and Opal Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog | White color tunable.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|----------------------|-----------------------------|-----------|
| DL1005RFXXN007N000000000T | 7        | 120        | 100   100            | 110   100   50              | 1750      |
| DL1005RFXXN012N000000000T | 12       | 120        | 100   100            | 110   100   50              | 1750      |
| DL1006RFXXN015N000000000T | 15       | 120        | 135   135            | 145   145   58              | 2250      |
| DL1006RFXXN018N000000000T | 18       | 120        | 135   135            | 145   145   58              | 2250      |



## SWANK S DL0075 (SURFACE/SUSPENDED DOWNLIGHT)

Arraystorm SWANK, Surface/Suspended Mounted High Efficiency LED Round Downlight, Body made of Aluminium and Opal Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog | White color tunable.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| DL0075FFXXN010N165000000 | 10       | 120        | 75   165                    | 2400      |
| DL0075FFXXN015N165000000 | 15       | 120        | 75   165                    | 2750      |
| DL0075FFXXN018N165000000 | 18       | 120        | 75   165                    | 3000      |
| DL0075SFXXN010N100000000 | 10       | 120        | 75   100                    | 3000      |
| DL0075SFXXN015N100000000 | 15       | 120        | 75   100                    | 3250      |
| DL0075SFXXN018N100000000 | 18       | 120        | 75   100                    | 3500      |



## SWANK S DL0100 (SURFACE/SUSPENDED DOWNLIGHT)

Arraystorm SWANK S100 Surface/Suspended Mounted High Efficiency LED Round Downlight, Body made of Aluminium and Opal Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog | White color tunable.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>W   H | MRP (INR) |
|--------------------------|----------|------------|-------------------------|-----------|
| DL0100FFXXN015N165000000 | 15       | 120        | 100   165               | 2750      |
| DL0100FFXXN018N165000000 | 18       | 120        | 100   165               | 3000      |
| DL0100FFXXN024N190000000 | 24       | 120        | 100   190               | 4250      |
| DL0100FFXXN030N190000000 | 30       | 120        | 100   190               | 4500      |
| DL0100SFXXN015N100000000 | 15       | 120        | 100   100               | 3000      |
| DL0100SFXXN018N100000000 | 18       | 120        | 100   100               | 3250      |
| DL0100SFXXN024N100000000 | 24       | 120        | 100   100               | 4250      |
| DL0100SFXXN030N100000000 | 30       | 120        | 100   100               | 4500      |



## SWANK S DL0150 (SURFACE/SUSPENDED DOWNLIGHT)

Arraystorm SWANK S150 Surface/Suspended Mounted High Efficiency LED Round Downlight, Body made of Aluminium and Opal Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog | White color tunable.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| DL0150FFXXN010N080000000 | 10       | 120        | 150   80                    | 2500      |
| DL0150FFXXN015N080000000 | 15       | 120        | 150   80                    | 2750      |
| DL0150FFXXN018N080000000 | 18       | 120        | 150   80                    | 3000      |
| DL0150FFXXN024N080000000 | 24       | 120        | 150   80                    | 3500      |
| DL0150SFXXN015N080000000 | 15       | 120        | 150   80                    | 3250      |
| DL0150SFXXN018N080000000 | 18       | 120        | 150   80                    | 3500      |
| DL0150SFXXN024N080000000 | 24       | 120        | 150   80                    | 4000      |



GREEN  
BLDC  
55%  
16000

NR  
FANS | LIGHTING | APPLIANCES

 **Arraystorm**  
Sense the future

 **Arraystorm**  
Sense the future



# LINEAR CHANNEL



## LINEAGE R CL4535 (RECESSED CHANNEL)

Arraystorm LINEAGE R CL4535 High Efficiency Recessed LED Channel, Body made of extruded Aluminium and PMMA Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog | White color tunable.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|----------------------|-----------------------------|-----------|
| CL4535RFXXN010N2FS000000 | 10       | 120        | 595   40             | 600   45   35               | 2500      |
| CL4535RFXXN020N4FS000000 | 20       | 120        | 1190   40            | 1995   45   35              | 4500      |
| CL4535RFXXN040N8FS000000 | 40       | 120        | 2380   40            | 2385   45   35              | 6750      |
| CL4535RFXXN056N8FS000000 | 56       | 120        | 2380   40            | 2385   45   35              | 7750      |



## LINEAGE R CL4535CM (RECESSED CHANNEL WITH COLLIMETRIC LENS)

Arraystorm LINEAGE R 4535 CM, High Efficiency Recessed LED Channel, Body made of extruded Aluminium and PMMA Diffuser with Optics of Collimetric dark optics Lens Rectangular distribution.

230 V with standard driver, CRI>80  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|----------------------|-----------------------------|-----------|
| CL4535RFXXN010N2FS00CM00 | 10       | 90         | 595   40             | 600   45   35               | 5500      |
| CL4535RFXXN020N4FS00CM00 | 20       | 90         | 1190   40            | 1995   45   35              | 10250     |
| CL4535RFXXN040N8FS00CM00 | 40       | 90         | 2380   40            | 2385   45   35              | 17750     |
| CL4535RFXXN056N8FS00CM00 | 56       | 90         | 2380   40            | 2385   45   35              | 19000     |



## LINEAGE R CL4535WW (RECESSED CHANNEL WITH WALL WASHER)

Arraystorm LINEAGE R 4535WW, High Efficiency Recessed LED Channel, Body made of extruded Aluminium and PMMA Diffuser with Optics of wall washer optics Lens Assymetric distribution.

230 V with standard driver, CRI>80  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|----------------------|-----------------------------|-----------|
| CL4535RFXXN010N2FS00WW00 | 10       | 60         | 595   40             | 600   45   35               | 8000      |
| CL4535RFXXN020N4FS00WW00 | 20       | 60         | 1190   40            | 1995   45   35              | 15000     |
| CL4535RFXXN040N8FS00WW00 | 40       | 60         | 2380   40            | 2385   45   35              | 27500     |
| CL4535RFXXN056N8FS00WW00 | 56       | 60         | 2380   40            | 2385   45   35              | 28500     |



## LINEAGE R CL6540 (RECESSED CHANNEL)

Arraystorm LINEAGE R 6540 High Efficiency Recessed LED Channel, Body made of extruded Aluminium and PMMA Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|----------------------|-----------------------------|-----------|
| CL6540RFXXN005N1FS000000 | 5        | 120        | 298   60             | 304   65   40               | 1750      |
| CL6540RFXXN010N2FS000000 | 10       | 120        | 595   60             | 600   65   40               | 3250      |
| CL6540RFXXN020N4FS000000 | 20       | 120        | 1190   60            | 1195   65   40              | 4750      |
| CL6540RFXXN040N8FS000000 | 40       | 120        | 2380   60            | 2385   65   40              | 8500      |
| CL6540RFXXN056N8FS000000 | 56       | 120        | 2380   60            | 2385   65   40              | 9250      |



## LINEAGE R CL8840 (RECESSED CHANNEL)

Arraystorm LINEAGE R 8840 High Efficiency Recessed LED Channel, Body made of extruded Aluminium and PMMA Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|----------------------|-----------------------------|-----------|
| CL8840RFXXN010N2FS000000 | 10       | 120        | 595   83             | 600   88   40               | 3500      |
| CL8840RFXXN020N4FS000000 | 20       | 120        | 1195   83            | 1200   88   40              | 5500      |
| CL8840RFXXN040N8FS000000 | 40       | 120        | 2380   83            | 2385   88   40              | 10000     |
| CL8840RFXXN056N8FS000000 | 56       | 120        | 2380   83            | 2385   88   40              | 10750     |



## LINEAGE S CL5285 (SUSPENDED CHANNEL)

Arraystorm LINEAGE S 5285 High Efficiency Suspended LED Channel, Body made of extruded Aluminium and Opal Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| CL5285SFXXN010N2FS000000 | 10       | 120        | 600   50   85               | 4000      |
| CL5285SFXXN020N4FS000000 | 20       | 120        | 1195   50   85              | 5500      |
| CL5285SFXXN040N8FS000000 | 40       | 120        | 2384   50   85              | 10250     |
| CL5285SFXXN056N8FS000000 | 56       | 120        | 2385   50   85              | 11000     |



## LINEAGE S CL5285 (SUSPENDED CHANNEL JOINERIES)

Arraystorm LINEAGE S 5285 High Efficiency Suspended LED Channel Joineries, Body made of extruded Aluminium and Opal Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.



| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| CL5285SFXXN010N1FL000000 | 10       | 120        | 325   325   85              | 4500      |
| CL5285SFXXN010N1FV000000 | 10       | 120        | 325   325   85              | 6500      |
| CL5285SFXXN015N1FY000000 | 15       | 120        | 300   300   85              | 10250     |
| CL5285SFXXN015N1FT000000 | 15       | 120        | 600   325   85              | 10250     |
| CL5285SFXXN020N1FP000000 | 20       | 120        | 600   600   85              | 11750     |



## LINEAGE S CL5293 (DEEP INSET SUSPENDED CHANNEL)

Arraystorm LINEAGE S 5293 High Efficiency Deep Inset Suspended LED Channel, Body made of extruded Aluminium and Opal Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| CL5293SFXXN010N2FS000000 | 10       | 120        | 600   50   93               | 4250      |
| CL5293SFXXN020N4FS000000 | 20       | 120        | 1195   50   93              | 6500      |
| CL5293SFXXN040N8FS000000 | 40       | 120        | 2385   50   93              | 11500     |
| CL5293SFXXN056N8FS000000 | 56       | 120        | 2385   50   93              | 12250     |



## LINEAGE S CL5293 (DEEP INSET SUSPENDED CHANNEL JOINERIES)

Arraystorm LINEAGE S 5293 High Efficiency Suspended LED Channel Joineries, Body made of extruded Aluminium and Opal Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.



| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| CL5293SFXXN010N1FL000000 | 10       | 120        | 325   325   93              | 4750      |
| CL5293SFXXN010N1FV000000 | 10       | 120        | 325   325   93              | 6750      |
| CL5293SFXXN015N1FY000000 | 15       | 120        | 300   300   93              | 11500     |
| CL5293SFXXN015N1FT000000 | 15       | 120        | 600   325   93              | 11500     |
| CL5293SFXXN020N1FP000000 | 20       | 120        | 600   600   93              | 12750     |



## LINEAGE S CL5285 CM (SUSPENDED CHANNEL WITH COLLIMETRIC LENS)

Arraystorm LINEAGE S 5285 CM, High Efficiency Suspended LED Channel, Body made of extruded Aluminium and PMMA Diffuser with Optics of Collimetric dark optics Lens Rectangular distribution.

230 V with standard driver, CRI>80  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| CL5285SFXXN010N2FS01CM00 | 10       | 90         | 600   50   85               | 7500      |
| CL5285SFXXN020N4FS01CM00 | 20       | 90         | 1195   50   85              | 12750     |
| CL5285SFXXN040N8FS01CM00 | 40       | 90         | 2385   50   85              | 29250     |
| CL5285SFXXN056N8FS01CM00 | 56       | 90         | 2385   50   85              | 30500     |



## LINEAGE S CL5285 HC (SUSPENDED CHANNEL WITH HONEYCOMB LOUVER)

Arraystorm LINEAGE S 5285 HC, High Efficiency Suspended LED Channel, Body made of extruded Aluminium and PMMA Diffuser with Optics of Honeycomb.

230 V with standard driver, CRI>80  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| CL5285SFXXN020N2FS01HC00 | 20       | 90         | 600   50   85               | 5,250     |
| CL5285SFXXN040N4FS01HC00 | 40       | 90         | 1195   50   85              | 9000      |
| CL5285SFXXN080N8FS01HC00 | 80       | 90         | 2385   50   85              | 14250     |



## LINEAGE S CL5285 LU (SUSPENDED CHANNEL WITH CROSS LOUVERS)

Arraystorm LINEAGE S 5285 LU, High Efficiency Suspended LED Channel, Body made of extruded Aluminium and PMMA Diffuser with Optics of Cross Louver Lens.

230 V with standard driver, CRI>80  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| CL5285SFXXN020N2FS01LU00 | 20       | 90         | 600   50   85               | 5750      |
| CL5285SFXXN040N4FS01LU00 | 40       | 90         | 1195   50   85              | 9500      |
| CL5285SFXXN080N8FS01LU00 | 80       | 90         | 2385   50   85              | 15750     |



## LINEAGE S CL5285 WW (SUSPENDED CHANNEL WITH WALL WASHER)

Arraystorm LINEAGE S 5285 WW, High Efficiency Suspended LED Channel, Body made of extruded Aluminium and PMMA Diffuser with Optics of Wall Washer Lens.

230 V with standard driver, CRI>80  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| CL5285SFXXN010N2FS01WW00 | 10       | 60         | 600   50   85               | 9250      |
| CL5285SFXXN020N4FS01WW00 | 20       | 60         | 1195   50   85              | 16750     |
| CL5285SFXXN040N8FS01WW00 | 40       | 60         | 2385   50   85              | 37000     |



## LINEAGE S CL5285 CU (SUSPENDED CURVILINEAR CHANNEL)

5293 High Efficiency Suspended Curvilinear LED Channel, Body made of extruded Aluminium and Opal Diffuser with homogeneous light distribution, low glare and without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| CL5285SFXXN020N1MT00CU50 | 20       | 120        | 1000   50   85              | 14500     |





## LINEAGE S CL5085 (SUSPENDED TRIMLESS CHANNEL)

Arraystorm LINEAGE S 5085 High Efficiency Suspended Trimless LED Channel, Body made of extruded Aluminium and Opal flexible Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| CL5085SFXXN010N2FS000000 | 10       | 120        | 600   50   85               | 4250      |
| CL5085SFXXN020N4FS000000 | 20       | 120        | 1195   50   85              | 6750      |
| CL5085SFXXN040N8FS000000 | 40       | 120        | 2385   50   85              | 11500     |
| CL5085SFXXN056N8FS000000 | 56       | 120        | 2385   50   85              | 12500     |



## LINEAGE S CL5085 (SUSPENDED CHANNEL JOINERIES)

Arraystorm LINEAGE S 5085 High Efficiency Suspended LED Channel Joineries, Body made of extruded Aluminium and Opal Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.



| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| CL5085SFXXN010N1FLO00000 | 10       | 120        | 325   325   85              | 4750      |
| CL5085SFXXN010N1FV000000 | 10       | 120        | 325   325   85              | 6750      |
| CL5085SFXXN015N1FY000000 | 15       | 120        | 300   300   85              | 11500     |
| CL5085SFXXN015N1FT000000 | 15       | 120        | 600   325   85              | 11500     |
| CL5085SFXXN020N1FP000000 | 20       | 120        | 600   600   85              | 12750     |



## LINEAGE S CL7585 (SUSPENDED CHANNEL)

Arraystorm LINEAGE S CL7585 High Efficiency Suspended LED Channel, Body made of extruded Aluminium and Opal Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| CL7585SFXXN014N2FS000000 | 14       | 120        | 600   75   85               | 5250      |
| CL7585SFXXN028N4FS000000 | 28       | 120        | 1195   75   85              | 7250      |
| CL7585SFXXN040N8FS000000 | 40       | 120        | 2385   75   85              | 12750     |
| CL7585SFXXN056N8FS000000 | 56       | 120        | 2385   75   85              | 14250     |



## LINEAGE S CL1085 (SUSPENDED CHANNEL)

Arraystorm LINEAGE S CL1085 High Efficiency Suspended LED Channel, Body made of extruded Aluminium and Opal Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| CL1085SFXXN014N2FS000000 | 14       | 120        | 600   100   85              | 4500      |
| CL1085SFXXN028N4FS000000 | 28       | 120        | 1195   100   85             | 6750      |
| CL1085SFXXN040N8FS000000 | 40       | 120        | 2385   100   85             | 12000     |
| CL1085SFXXN056N8FS000000 | 56       | 120        | 2385   100   85             | 13000     |



## LINEAGE S CL1458 (SUSPENDED CHANNEL)

Arraystorm LINEAGE CL1458 High Efficiency Suspended LED Channel, Body made of extruded Aluminium and Opal Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| CL1458SFXXN030N4FS000000 | 30       | 120        | 1195   145   58             | 10500     |
| CL1458SFXXN040N8FS000000 | 40       | 120        | 2395   145   58             | 14000     |
| CL1458SFXXN056N8FS000000 | 56       | 120        | 2395   145   58             | 15500     |



## LINEAGE S CL5285 UD (SUSPENDED UP-DOWN CHANNEL)

Arraystorm LINEAGE S CL5285 High Efficiency Suspended Up-Down LED Channel, Body made of extruded Aluminium and Opal Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| CL5285UDXXN009N2FS000500 | 14       | 120        | 600   50   85               | 5250      |
| CL5285UDXXN020N4FS000800 | 28       | 120        | 1195   50   85              | 7500      |
| CL5285UDXXN040N8FS001600 | 56       | 120        | 2385   50   85              | 12500     |
| CL5285UDXXN056N8FS002400 | 80       | 120        | 2385   50   85              | 14000     |



## LINEAGE S CL5293 UD (SUSPENDED DEEP INSET UP-DOWN CHANNEL)

Arraystorm LINEAGE S CL5293 High Efficiency Suspended Deep Inset Up-Down LED Channel, Body made of extruded Aluminium and Opal Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| CL5293UDXXN009N2FS000500 | 14       | 120        | 600   50   93               | 4250      |
| CL5293UDXXN020N4FS000800 | 28       | 120        | 1195   50   93              | 6500      |
| CL5293UDXXN040N8FS001600 | 56       | 120        | 2385   50   93              | 11000     |
| CL5293SFUDN056N8FS002400 | 80       | 120        | 2385   50   93              | 12250     |



## LINEAGE S CL5085 UD (SUSPENDED UP-DOWN CHANNEL)

Arraystorm LINEAGE S CL5085 High Efficiency Suspended Up-Down LED Channel, Body made of extruded Aluminium and Opal Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| CL5085UDXXN009N2FS000500 | 14       | 120        | 600   50   85               | 5750      |
| CL5085UDXXN020N4FS000800 | 28       | 120        | 1195   50   85              | 8250      |
| CL5085UDXXN040N8FS001600 | 56       | 120        | 2385   50   85              | 13500     |
| CL5085UDXXN056N8FS002400 | 80       | 120        | 2385   50   85              | 14500     |



## LINEAGE S CL7585 UD (SUSPENDED UP-DOWN CHANNEL)

Arraystorm LINEAGE S CL7585 UD High Efficiency Suspended Up-Down LED Channel, Body made of extruded Aluminium and Opal Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| CL7585UDXXN014N2FS000600 | 20       | 120        | 600   75   85               | 5750      |
| CL7585UDXXN028N4FS001200 | 40       | 120        | 1195   75   85              | 8250      |
| CL7585UDXXN040N8FS001600 | 56       | 120        | 2385   75   85              | 15000     |
| CL7585UDXXN056N8FS002400 | 80       | 120        | 2385   75   85              | 16500     |



## LINEAGE S CL1085 UD (SUSPENDED UP-DOWN CHANNEL)

Arraystorm LINEAGE S CL1085 UD High Efficiency Suspended Up-Down LED Channel, Body made of extruded Aluminium and Opal Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| CL1085UDXXN014N2FS000600 | 20       | 120        | 600   100   85              | 6750      |
| CL1085UDXXN028N4FS001200 | 40       | 120        | 1195   100   85             | 12000     |
| CL1085UDXXN040N8FS001600 | 56       | 120        | 2385   100   85             | 16000     |
| CL1085UDXXN056N8FS002400 | 80       | 120        | 2385   100   85             | 18000     |



## LINEAGE S CL1458 UD (SUSPENDED UP-DOWN CHANNEL)

Arraystorm LINEAGE S CL1458 UD High Efficiency Suspended LED Up-Down Channel, Body made of extruded Aluminium and Opal Diffuser with homogeneous light distribution and without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| CL1458UDXXN028N4FS001200 | 40       | 120        | 1195   145   58             | 12250     |
| CL1458UDXXN040N8FS001600 | 56       | 120        | 2385   145   58             | 16250     |
| CL1458UDXXN056N8FS002400 | 80       | 120        | 2385   145   58             | 17500     |



# ARCHITECTURAL



## FABIA AR0301 UD/ AR0301 SF (ONLY DOWN SUSPENDED UP-DOWN ARCHITECTURAL)

Arraystorm FABIA AR0301 UD High Efficiency Architectural Up-Down LED Suspended luminaire, Body made of high grade Aluminium in Matt White powder coated and extremely smooth homogeneous light across the transparent acrylic diffuser without hot spots.

230V, CRI>80, Color Temperature 3000K/4000K/5700K.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| AR0301UDXXN020S4FS002000 | 40       | 120        | 1198   220   8              | 24500     |
| AR0301UDXXN040S8FS004000 | 80       | 120        | 2396   220   8              | 39000     |
| AR0301SFXXN040N4FS000000 | 40       | 120        | 1198   220   8              | 20500     |
| AR0301SFXXN080N8FS000000 | 80       | 120        | 2396   220   8              | 35000     |



## STEALTH AR2140 UD / AR2140 SF (ONLY DOWN SUSPENDED UP-DOWN ARCHITECTURAL)

Arraystorm STEALTH AR2140 UD High Efficiency Architectural Up-Down LED Suspended luminaire, Body made of high grade Aluminium in Matt White powder coated and extremely smooth homogeneous light across the transparent acrylic diffuser without hot spots.

230V, CRI>80, Color Temperature 3000K/4000K/5700K.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| AR2140UDXXN030N4FS001600 | 46       | 120        | 1260   210   62             | 25000     |
| AR2140UDXXN040N8FS002400 | 64       | 120        | 2376   210   62             | 48750     |
| AR2140SFXXN030N4FS000000 | 30       | 120        | 1260   210   62             | 22500     |
| AR2140SFXXN060N8FS000000 | 60       | 120        | 2376   210   62             | 44750     |



## BARNEY PN0401 (PENDANT LIGHT)

Arraystorm Barney PN0401 is Suspended LED Architectural pendant Light, Body made of high- grade extruded Aluminium available in Matt White,Red, Black, Orange & Blue, with Polycarbonate diffuser for bright & homogeneous light.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>Dia   H | MRP (INR) |
|--------------------------|----------|------------|---------------------------|-----------|
| PN0401SFXXN028N000000000 | 28       | 120        | 400   210                 | 10750     |



## BARNEY DOME PN0501 (PENDANT LIGHT)

Arraystorm Barney Dome PN0501 is Suspended LED Architectural pendant Light, Body made of high- grade extruded Aluminium, with Opal diffuser for bright & homogeneous light.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>Dia   H | MRP (INR) |
|--------------------------|----------|------------|---------------------------|-----------|
| PN0501SFXXN035N000000000 | 35       | 120        | 500   334                 | 12250     |



## ARIUM MESH AR8021 (LED DRUM LIGHT)

Arraystorm Arium Mesh Drum is Suspended LED Architectural pendant Light, Body made of perforated CRCA with Opal diffuser for bright & homogeneous light.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>Dia   H | MRP (INR) |
|--------------------------|----------|------------|---------------------------|-----------|
| AR8021SFXXN030N450010000 | 30       | 120        | 450   210                 | 13750     |



## ARIUM 2 (LED DRUM LIGHT)

Arraystorm Arium 2, Hi-efficiency Suspended LED Drum Luminaire made of High - grade extruded Aluminium housing in Matt White color. Screwless and seamless circumference and extremely smooth homogeneous light through the frosted unbreakable polycarbonate diffuser, without hot spots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>Dia   H | MRP (INR) |
|---------------------------|----------|------------|---------------------------|-----------|
| AR8010SFXXN024N3000010000 | 24       | 120        | 300   60                  | 8000      |
| AR8011SFXXN030N4000000000 | 30       | 120        | 450   60                  | 14500     |
| AR8012SFXXN040N6000000000 | 40       | 120        | 600   60                  | 19500     |
| AR8013SFXXN060N7500000000 | 60       | 120        | 750   60                  | 28000     |
| AR8014SFXXN060N9000000000 | 60       | 120        | 900   60                  | 39000     |



## ARIUM 3 (LED DRUM LIGHT UP-DOWN LIGHT)

Arraystorm Arium 3, Hi-efficiency Suspended LED up-down Drum Luminaire made of High - grade extruded Aluminium housing in Matt White color. Screwless and seamless circumference and extremely smooth homogeneous light through the frosted unbreakable polycarbonate diffuser, without hot spots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>Dia   H | MRP (INR) |
|---------------------------|----------|------------|---------------------------|-----------|
| AR8010UDXXN024N3000001200 | 36       | 120        | 300   60                  | 9750      |
| AR8011UDXXN028N4500001200 | 40       | 120        | 450   60                  | 16500     |
| AR8012UDXXN040N6000001600 | 56       | 120        | 600   60                  | 21500     |
| AR8013UDXXN060N6000002400 | 84       | 120        | 750   60                  | 30500     |
| AR8014UDXXN060N9000002400 | 84       | 120        | 900   60                  | 41500     |



## ARIUM 4 (RECESSED DRUM LIGHT)

Arraystorm Arium 4, Hi-efficiency Recessed LED Drum Luminaire made of High - grade extruded Aluminium housing in Matt White color. Screwless and seamless circumference and extremely smooth homogeneous light through the frosted unbreakable polycarbonate diffuser, without hot spots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>Dia   H | MRP (INR) |
|---------------------------|----------|------------|---------------------------|-----------|
| AR8011RFXXN030N4500000000 | 30       | 120        | 450   60                  | 9500      |
| AR8012RFXXN040N6000000000 | 40       | 120        | 600   60                  | 15000     |



## ORBIZ (LED RING LIGHT)

Arraystorm Orbiz, Hi-efficiency Suspended LED Ring Luminaire made of high-grade extruded Aluminium housing in Matt White color. Screwless and seamless circumference and extremely smooth homogeneous light through the frosted unbreakable polycarbonate diffuser, without hot spots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>Dia   H | MRP (INR) |
|---------------------------|----------|------------|---------------------------|-----------|
| OR0600SFXXN040N0000000000 | 40       | 120        | 600   60                  | 23000     |
| OR0750SFXXN064N0000000000 | 64       | 120        | 750   60                  | 29750     |
| OR0900SF40N064N0000000000 | 64       | 120        | 900   60                  | 42500     |





## TRIA (TRIANGLE SHAPED)

Arraystorm Tria, Hi-efficiency Suspended LED Triangle Luminaire made of high-grade extruded aluminium housing in Matt White color. Screwless and seamless circumference and extremely smooth homogeneous light through the frosted unbreakable polycarbonate diffuser, without hot spots.

230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>Each side   H | MRP (INR) |
|--------------------------|----------|------------|---------------------------------|-----------|
| AR9302SFXXN030N1FT000000 | 30       | 120        | 300   300   300   60            | 21000     |
| AR9302SFXXN040N2FT000000 | 40       | 120        | 600   600   600   60            | 31750     |



## RHOMBIC AR9401 - (ROMBUS SHAPED)

Arraystorm Rhomic, Hi-efficiency Suspended LED Rhombus Luminaire made of high-grade extruded aluminium housing in Matt White color. Screwless and seamless circumference and extremely smooth homogeneous light through the frosted unbreakable polycarbonate diffuser, without hot spots.

230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>Each side   H | MRP (INR) |
|--------------------------|----------|------------|---------------------------------|-----------|
| AR9401SFXXN035N000000000 | 35       | 120        | 300   300   60                  | 27000     |



## Hexoid (Hexagon)

Arraystorm Hexoid, Hi-efficiency Suspended LED Hexagon Luminaire made of high-grade extruded aluminium housing in Matt White color. Screwless and seamless circumference and extremely smooth homogeneous light through the frosted unbreakable polycarbonate diffuser, without hot spots.

230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>Each side   H | MRP (INR) |
|---------------------------|----------|------------|---------------------------------|-----------|
| AR9101SFXXN040N30000000FG | 40       | 120        | 300   300   60                  | 18000     |
| AR9102SXXN080N60000000FG  | 80       | 120        | 600   600   60                  | 34500     |



## HEXOID RING (HEXAGON SHAPED RING)

Arraystorm Hexoid-Ring, Hi-efficiency Suspended LED Hexagon Ring Luminaire made of high-grade extruded aluminium housing in Matt White color. Screwless and seamless circumference and extremely smooth homogeneous light through the frosted unbreakable polycarbonate diffuser, without hot spots.

230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>Each side   W   H | MRP (INR) |
|--------------------------|----------|------------|-------------------------------------|-----------|
| AR9201SFXXN030N3000000RG | 30       | 120        | 300   300   50   85                 | 22000     |
| AR9202SFXXN060N6000000RG | 60       | 120        | 600   600   50   85                 | 30500     |



## TRAPEZE GL4006 (TRAPEZOID)

Arraystorm Trapezoid, Hi-efficiency Suspended LED Trapezium Luminaire made of high-grade aluminium housing in Matt White color. Screwless and seamless circumference and extremely smooth homogeneous light through the frosted unbreakable polycarbonate diffuser, without hot spots.

230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| GL4006SFXXN028N000000000 | 28       | 120        | 1192   395   195   60       | 15500     |



## SABER BT9002 (COMMERCIAL BATTEN 20W)

Arraystorm SABER LED Batten 20W, Body made of Aluminium and Acrylic Diffuser.

CRI>80,  
CCT available in 3000K/4000K/5700K

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| BT9002SFXXN010N2FS000000 | 10       | 120        | 600   30   35               | 700       |
| BT9002SFXXN020N4FS000000 | 20       | 120        | 1200   30   35              | 1050      |



## SABER BT9004 (COMMERCIAL BATTEN 40W)

Arraystorm SABER LED Batten 40W, Body made of Aluminium and Acrylic Diffuser.

CRI>80,  
CCT available in 3000K/4000K/5700K.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| BT9004SFXXN020N2FS000000 | 20       | 120        | 600   42   48               | 1050      |
| BT9004SFXXN040N4FS000000 | 40       | 120        | 1200   42   48              | 1750      |



## BANDSTORM (Strip Light)

Arraystorm BANDSTORM is Decorative LED IP 20 Striplight The LED striplight gives a smoothing effect.

5m/Spool,  
230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K. Driver also available in DALI

| PRODUCT CODE                  | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|-------------------------------|----------|------------|-----------------------------|-----------|
| STRIP LIGHT - IP20            |          |            |                             |           |
| SR7001SFXXX005N1MT000000T     | 4.8      | 120        | 5m/spool                    | 350       |
| SR7002SFXXX010N1MT000000T     | 9.6      | 120        | 5m/spool                    | 450       |
| SR7003SFXXX015N1MT000000T     | 14.4     | 120        | 5m/spool                    | 650       |
| STRIP LIGHT - IP65            |          |            |                             |           |
| SR7011SFXXX005N1MT000000T     | 4.8      | 120        | 5m/spool                    | 700       |
| SR7012SFXXX010N1MT000000T     | 9.6      | 120        | 5m/spool                    | 750       |
| SR7013SFXXX015N1MT000000T     | 14.4     | 120        | 5m/spool                    | 900       |
| STRIP LIGHT - DRIVER          |          |            |                             |           |
| 112812250000                  | 30       | 120        | NA                          | 850       |
| 112812400000                  | 48       | 120        | NA                          | 1500      |
| 112812600000                  | 72       | 120        | NA                          | 2500      |
| STRIP LIGHT - SURFACE CHANNEL |          |            |                             |           |
| CL1707SFXXNXXXN1MT000000T     | NA       | 120        | 1000   17   7               | 400       |
| CL1714SFXXNXXXN1MT000000T     | NA       | 120        | 1000   17   14              | 500       |
| STRIP LIGHT - RECESS CHANNEL  |          |            |                             |           |
| CL2507RFXXNXXXN1MT000000T     | NA       | 120        | 1000   25   7               | 550       |
| CL2514RFXXNXXXN1MT000000T     | NA       | 120        | 1000   25   14              | 650       |



The image shows a modern retail clothing store interior. In the background, there are long wooden racks filled with various shirts and sweaters. To the left, there are shelves displaying folded clothes and accessories. In the foreground, a long wooden table serves as a display area for more clothing items and boxes. The floor is made of large, light-colored tiles. The ceiling is equipped with track lighting. The entire image is overlaid with large, diagonal orange geometric shapes. A white rectangular box is centered over the image, containing the word "RETAIL" in large, bold, white capital letters.

# RETAIL



## METEOR 1 (FIXED RECESS SPOT LIGHT)

Arraystorm METEOR 1 is Recessed Fixed LED Spotlight, Body made of high grade die-cast Aluminium.

230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE     | CUTOUT (mm) Dia | DIMENSION (mm) Dia   H | MRP (INR) |
|---------------------------|----------|----------------|-----------------|------------------------|-----------|
| SL3000RFXXN003N000000000T | 3        | 24             | 35              | 40   36                | 950       |
| SL3001RFXXN007N0000000000 | 7        | 15, 24, 36,    | 60              | 68   65                | 1500      |
| SL3002RFXXN012N0000000000 | 12       | 15, 24, 60     | 75              | 83   74                | 1700      |
| SL3003RFXXN018N0000000000 | 18       | 15, 24, 36, 60 | 86              | 95   90                | 2300      |
| SL3003RFXXN024N0000000000 | 24       | 15, 24, 36, 60 | 86              | 95   90                | 2900      |
| SL3004RFXXN030N0000000000 | 30       | 15, 24, 36, 60 | 100             | 115   105              | 3500      |
| SL3004RFXXN036N0000000000 | 36       | 15, 24, 36, 60 | 100             | 115   105              | 3750      |



## METEOR 1 GLOW (FIXED RECESS SPOT LIGHT)

Arraystorm METEOR 1 Glow is Recessed Fixed LED Spotlight, Body made of high grade die-cast Aluminium.

230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE     | CUTOUT (mm) Dia | DIMENSION (mm) Dia   H | MRP (INR) |
|---------------------------|----------|----------------|-----------------|------------------------|-----------|
| SL3093RFXXN010N000000000T | 10       | 15, 24, 36     | 68              | 80   62                | 1750      |
| SL3094RFXXN020N000000000T | 20       | 15, 24, 36, 60 | 95              | 108   70               | 2000      |



## METEOR 2 DR (TILTABLE DEEP INSET RECESS SPOT LIGHT)

Arraystorm METEOR 2 is Recessed adjustable LED Spotlight, Body made of high grade di-cast Aluminium.

230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | CUTOUT (mm) Dia | DIMENSION (mm) Dia   H | MRP (INR) |
|---------------------------|----------|------------|-----------------|------------------------|-----------|
| SL3110RMXXN003N000000000T | 3        | 40         | 43              | 52   45                | 1400      |
| SL3111RMXXN007N000000000T | 7        | 24, 38, 60 | 72              | 78   65                | 2000      |
| SL3112RMXXN012N000000000T | 12       | 24, 38, 60 | 80              | 88   75                | 2250      |
| SL3113RMXXN018N000000000T | 18       | 24, 38, 60 | 94              | 100   97               | 2750      |
| SL3113RMXXN024N000000000T | 24       | 24, 38, 60 | 94              | 100   97               | 3000      |
| SL3114RMXXN030N000000000T | 30       | 24, 38, 60 | 113             | 120   101              | 3750      |
| SL3114RMXXN036N000000000T | 36       | 24, 38, 60 | 113             | 120   101              | 4250      |



## METEOR 3 (DARK OPTICS RECESS SPOT LIGHT)

Arraystorm METEOR 3 Recessed Fixed LED Spotlight with Dark Optics, Body made of Aluminium high grade di-cast Aluminium.

230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | CUTOUT (mm) Dia | DIMENSION (mm) Dia   H | MRP (INR) |
|--------------------------|----------|------------|-----------------|------------------------|-----------|
| SL3021RFXXN007N000000000 | 7        | 24, 36, 60 | 65              | 74   68                | 2250      |
| SL3022RFXXN012N000000000 | 12       | 24, 36, 60 | 76              | 85   78                | 2500      |
| SL3023RFXXN018N000000000 | 18       | 24, 36, 60 | 95              | 100   95               | 4500      |
| SL3023RFXXN024N000000000 | 24       | 24, 36, 60 | 95              | 100   95               | 5000      |



## METEOR 1 WW (RECESS WALL WASHER SPOT LIGHT)

Arraystorm METEOR 1 WW is Recessed Fixed LED Wall Washer Spotlight, Body made of high grade die-cast Aluminium.

230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | CUTOUT (mm) Dia | DIMENSION (mm) Dia   H | MRP (INR) |
|---------------------------|----------|------------|-----------------|------------------------|-----------|
| SL3091RFXXN010N00000WW00T | 10       | 60         | 72              | 85   70                | 4000      |
| SL3092RFXXN020N00000WW00T | 20       | 60         | 92              | 108   86               | 4750      |



## CYLINDRICAL METEOR 5 FIXED (SUSPENDED SPOT LIGHT)

Arraystorm METEOR 5 is Surfaced/Suspended Fixed LED Cylindrical Spotlight, Body made of high grade extruded aluminium.

230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm) Dia   H | MRP (INR) |
|--------------------------|----------|------------|------------------------|-----------|
| CYLINDER 50mm            |          |            |                        |           |
| SL3041SFXXN006N165000000 | 6        | 24, 36, 60 | 50   165               | 3250      |
| CYLINDER 70mm            |          |            |                        |           |
| SL3042SFXXN015N165000000 | 15       | 24, 36, 60 | 70   165               | 4000      |
| SL3042SFXXN018N165000000 | 18       | 24, 36, 60 | 70   165               | 4250      |
| CYLINDER 100mm           |          |            |                        |           |
| SL3043SFXXN015N165000000 | 15       | 24, 36, 60 | 100   165              | 4500      |
| SL3043SFXXN018N165000000 | 18       | 24, 36, 60 | 100   165              | 4750      |
| SL3043SFXXN024N190000000 | 24       | 24, 36, 60 | 100   190              | 5500      |
| SL3043SFXXN030N190000000 | 30       | 24, 36, 60 | 100   190              | 6500      |



## CYLINDRICAL METEOR 5 FIXED DARK OPTICS (COLOR TRIM, SUSPENDED SPOT)

Arraystorm METEOR 5 is Surfaced/Suspended Fixed LED Cylindrical Spotlight with Dark Optics, Body made of high grade extruded aluminium.

230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>Dia   H | MRP (INR) |
|--------------------------|----------|------------|---------------------------|-----------|
| SL3042SFXXN015N0000000CT | 15       | 24, 36, 60 | 70   165                  | 4250      |



## CYLINDRICAL METEOR 5 FIXED WALL WASHER (SUSPENDED SPOT LIGHT)

Arraystorm METEOR 5 is Surfaced/Suspended Fixed LED Cylindrical Spotlight with Dark Optics, Body made of high grade extruded aluminium.

230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>Dia   H | MRP (INR) |
|---------------------------|----------|------------|---------------------------|-----------|
| SL3042SFXXN015N000000WW00 | 15       | 60         | 70   165                  | 9500      |



## METEOR 1 SQUARE SPOT (LOW GLARE LASER SPOT LIGHT)

Arraystorm METEOR 1 SQUARE Spot is Recessed Fixed LED Square Spotlight, Body made of high grade di-cast Aluminium.

230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.



| PRODUCT CODE              | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|----------------------|-----------------------------|-----------|
| SL3051RFXXN002N000000000T | 2        | 15, 30, 55 | 40   40              | 45   45   49                | 2250      |
| SL3052RFXXN005N000000000T | 5        | 15, 30, 55 | 70   40              | 75   45   49                | 3250      |
| SL3053RFXXN010N000000000T | 10       | 15, 30, 55 | 140   40             | 147   45   49               | 4250      |
| SL3054RFXXN020N000000000T | 20       | 15, 30, 55 | 275   40             | 280   45   49               | 9000      |
| SL3055RFXXN030N000000000T | 30       | 15, 30, 55 | 410   40             | 415   45   49               | 13000     |



## METEOR 1 SQUARE SPOT LIGHT (LOW GLARE LASER SPOT LIGHT)

Arraystorm METEOR SQUARE is Recessed Fixed LED Square Spotlight, Body made of high grade di-cast Aluminium.

230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog/




| PRODUCT CODE              | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|----------------------|-----------------------------|-----------|
| SL3056RFXXN004N000000000T | 4        | 38         | 42   42              | 52   52   56                | 1750      |
| SL3057RFXXN012N000000000T | 12       | 38         | 120   42             | 128   52   56               | 2750      |
| SL3058RFXXN016N000000000T | 16       | 38         | 80   80              | 90   90   56                | 3000      |
| SL3059RFXXN020N000000000T | 20       | 38         | 195   42             | 205   52   56               | 3500      |



## METEOR 1 SQUARE SPOT LIGHT (LOW GLARE LASER SPOT LIGHT)

Arraystorm METEOR SQUARE is Recessed Fixed LED Square Spotlight, Body made of high grade di-cast Aluminium.

230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.



| PRODUCT CODE              | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|----------------------|-----------------------------|-----------|
| SL3062RFXXN004N000000000T | 4        | 30         | 46   26              | 52   32   40                | 1250      |
| SL3063RFXXN006N000000000T | 6        | 30         | 56   26              | 62   32   40                | 1500      |
| SL3064RFXXN008N000000000T | 8        | 30         | 46   46              | 52   52   40                | 1750      |
| SL3065RFXXN010N000000000T | 10       | 30         | 102   26             | 108   32   40               | 2250      |
| SL3066RFXXN015N000000000T | 15       | 30         | 65   65              | 71   71   40                | 2500      |
| SL3067RFXXN020N000000000T | 20       | 30         | 198   26             | 204   32   40               | 3250      |



## VANTAGE GM9042 (GIMBALL 2X12 W)

Arraystorm VANTAGE Recessed LED Gimbal spotlight, Body made of Aluminium and Anodised Aluminium Reflector.

230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE   | CUTOUT (mm) L   W | DIMENSION (mm) L   W   H | MRP (INR) |
|--------------------------|----------|--------------|-------------------|--------------------------|-----------|
| GM9042RMXXN024N000000000 | 24       | 24   36   48 | 175   90          | 185   100   80           | 6,500     |



## OMNISENSE (TRACK LIGHT)

Arraystorm OMNISENSE 1 high power LED Tracklight, Body made of Aluminium and plastic enclosure.

230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE   | CUTOUT (mm) L   W | DIMENSION (mm) L   W | MRP (INR) |
|---------------------------|----------|--------------|-------------------|----------------------|-----------|
| TRACK LIGHT               |          |              |                   |                      |           |
| TL1102TMXXN010N2WR000000T | 10       | 24   36   48 | NA                | 49   100             | 2750      |
| TL1103TMXXN020N2WR000000T | 20       | 24   36   48 | NA                | 60   135             | 4500      |
| TL1104TMXXN030N2WR000000T | 30       | 24   36   48 | NA                | 80   150             | 5500      |
| TRACK RAIL                |          |              |                   |                      |           |
| TR1122FFXXNXXXNIMT000000T | NA       | NA           | NA                | 1000   35   20       | 1850      |
| TR1123FFXXNXXXNIMT000000T | NA       | NA           | NA                | 1000   35   20       | 2150      |
| TR1124FFXXNXXXNIMT000000T | NA       | NA           | NA                | 1000   35   20       | 2550      |
| TR1126FFXXNXXXNIMT000000T | NA       | NA           | NA                | 1000   35   20       | 4150      |
| TRACK RAIL ACCESSORIES    |          |              |                   |                      |           |
| ASTL1122ECAP              | NA       | NA           | NA                | NA                   | 100       |
| ASTL1122LEND              | NA       | NA           | NA                | NA                   | 750       |
| ASTL1122INJI              | NA       | NA           | NA                | NA                   | 750       |
| ASTL1122LJOI              | NA       | NA           | NA                | NA                   | 1000      |
| ASTL1122TJOI              | NA       | NA           | NA                | NA                   | 1250      |
| ASTL1122PJOI              | NA       | NA           | NA                | NA                   | 1500      |



## METEOR 1 MAGNETIC (LOW GLARE LASER SPOT LIGHT)

Arraystorm METEOR SQUARE is Magnetic rail mounted Fixed LED Square Spotlight, Body made of high grade di-cast Aluminium.

230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE   | DIMENSION (mm)<br>Dia   H | MRP (INR) |
|---------------------------|----------|--------------|---------------------------|-----------|
| SL3065TMXXN010NMAG010000T | 10       | 15   30   55 | 112   22   44             | 2250      |
| SL3067TMXXN020NMAG010000T | 20       | 15   30   55 | 220   22   44             | 2500      |



## METEOR 2 MAGNETIC (LOW GLARE LASER TILTABLE SPOT LIGHT)

Arraystorm METEOR SQUARE is Magnetic rail mounted Tiltable LED Square Spotlight, Body made of high grade di-cast Aluminium.

230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE   | DIMENSION (mm)<br>Dia   H | MRP (INR) |
|---------------------------|----------|--------------|---------------------------|-----------|
| SL3065TMXXN010NMAG0100MVT | 10       | 15   30   55 | 112   22   102            | 2500      |
| SL3067TMXXN020NMAG0100MVT | 20       | 15   30   55 | 220   22   102            | 3000      |



## OMNISENSE MAGNETIC (TRACK LIGHT)

Arraystorm OMNISCIENCE 3 is Magnetic rail mounted LED Tracklight, Body made of high grade di-cast Aluminium.

230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE   | DIMENSION (mm)<br>Dia   H | MRP (INR) |
|---------------------------|----------|--------------|---------------------------|-----------|
| TL1131TMXXN007NMAG010000T | 7        | 15   24   40 | 37   150                  | 2500      |
| TL1132TMXXN012NMAG010000T | 12       | 15   24   40 | 45   150                  | 3500      |



## METEOR 1 MAGNETIC WALL WASHER (LOW GLARE LASER SPOT LIGHT)

Arraystorm METEOR SQUARE is Magnetic rail mounted Tilttable LED Square WALL WASHER Spotlight, Body made of high grade di-cast Aluminium.

230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE   | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|--------------|-----------------------------|-----------|
| SL3065TMXXN010NMAG01WW00T | 10       | 15   30   55 | 132   22   44               | 2500      |
| SL3067TMXXN020NMAG01WW00T | 20       | 15   30   55 | 246   22   44               | 3000      |



## METEOR 1 DR MAGNETIC SPOT LIGHT (LOW GLARE DEEP INSET LASER)

Arraystorm METEOR SQUARE is Magnetic rail mounted Fixed LED Square Spotlight, Body made of high grade di-cast Aluminium.

230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog

| PRODUCT CODE              | WATT (W) | BEAM ANGLE   | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|--------------|-----------------------------|-----------|
| SL3071TMXXN008NMAG010000T | 8        | 15   30   55 | 112   22   102              | 4250      |
| SL3072TMXXN016NMAG010000T | 16       | 15   30   55 | 220   22   102              | 6250      |



## LINEAGE MAGNETIC CHANNEL LIGHT

Arraystorm LINEAGE CL2654 High Efficiency Magnetic Rail Mounted LED Channel, Body made of extruded Aluminium and Opal Diffuser with homogeneous light distribution and without hotspots

230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|-----------------------------|-----------|
| CL2654TMXXN010N1FS01MG00T | 10       | 120        | 203   22   44               | 2000      |
| CL2654TMXXN020N2FS01MG00T | 20       | 120        | 303   22   44               | 2250      |
| CL2654TMXXN030N2FLO1MG00T | 30       | 120        | 303   320   44              | 4000      |



## OMNISENSE MAGNETIC TRACK RAIL

Body made of high grade extruded Aluminium.



| PRODUCT CODE                     | WATT (W) | DESCRIPTION                                               | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|----------------------------------|----------|-----------------------------------------------------------|-----------------------------|-----------|
| MAGNETIC TRACK RAIL              |          |                                                           |                             |           |
| TR2654SFXXMAGX1MT014W00T         | NA       | Magnetic Suspended Track Rail TR2654                      | 1000   26   54              | 4250      |
| TR6347RFXXMAGX1MT014W00T         | NA       | Magnetic Recess Track Rail TR6354                         | 1000   63   47              | 4250      |
| MAGNETIC TRACK CONNECTORS        |          |                                                           |                             |           |
| TR6347RFLJOINTXXXXXXXXXXXT       | 10       | Magnetic Track Rail L Connector for Recess Track TR6324   |                             | 1750      |
| TR2654FFLJOINTXXXXXXXXXXXT       | 20       | Magnetic Track L Connector for Suspended TR2654           |                             | 1750      |
| MAGNETIC TRACK RAIL POWER SUPPLY |          |                                                           |                             |           |
| TR2654STCONNECTORXXXXXXXXXT      | NA       | Magnetic Track Rail straight Connector TR2654ST For Power |                             | 1000      |
| TR2654CORCONNECTORXXXXXXXXXT     | NA       | Magnetic Track Rail L Connector TR2654COR For Power       |                             | 1000      |
| TR26542INPUTCONNECTORXXXT        | NA       | Magnetic Track Rail Input Connector TR2654INPUT For Power |                             | 1000      |
| TR6347RFENDCAPXXXXXXXXXXXT       | NA       | Magnetic Track Rail End Cap for Recess Track TR6324ENDCAP |                             | 150       |
| TR2654FFENDCAPXXXXXXXXXXXT       | NA       | Magnetic Track End Cap for Suspended TR2654ENDCAP         |                             | 150       |
| MAGNETIC TRACK RAIL ACCESSORIES  |          |                                                           |                             |           |
| 112848200000                     | 100      | DC Power Supply 48 V, 2 A - 100W                          | 147   49   26               | 3500      |
| 112848400000                     | 200      | DC Power Supply 48 V, 4 A - 200W                          | 147   49   26               | 4750      |
| 112848800000                     | 400      | DC Power Supply 48 V, 8 A - 400W                          | 147   49   26               | 7000      |
| 112848200001                     | 100      | DC Power Supply 48 V, 2 A - 100W                          | Internal                    | 4000      |
| 112848400001                     | 200      | DC Power Supply 48 V, 4 A - 200W                          | Internal                    | 6500      |
| 117001500000                     | NA       | Arraystorm Suspension Wire 1.5 Mtrs Pair                  |                             | 1000      |

# PHOTOMETRIC LAB







# INDUSTRIAL



Arraystorm™  
Sense the future

IP65



## COB BAYSTORM -1 HB0901 (40 | 50W HIGHBAY)

Arraystorm COB BAYSTORM-1, Hi-efficiency LED LED low glare Highbay Luminaire, Body made of di-cast aluminium and hi-precision glass optics.

230 V with standard driver, CRI>70, CCT available in 3000K/4000K/5700K/6500K. Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| HB0901PFXXN040N000019065 | 40       | 60/90      | 180   180   240             | 6500      |
| HB0901PFXXN050N000019065 | 50       | 60/90      | 180   180   240             | 6750      |

IP65



## COB BAYSTORM -2 HB0902 (80 | 100W HIGHBAY)

Arraystorm COB BAYSTORM-2, Hi-efficiency LED LED low glare Highbay Luminaire, Body made of di-cast aluminium and hi-precision glass optics.

230 V with standard driver, CRI>70, CCT available in 3000K/4000K/5700K/6500K. Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| HB0902PFXXN080N000019065 | 80       | 60/90      | 180   365   240             | 12750     |
| HB0902PFXXN100N000019065 | 100      | 60/90      | 180   365   240             | 13000     |

IP65



## COB BAYSTORM -3 HB0903 (120 | 150W HIGHBAY)

Arraystorm COB BAYSTORM-3, Hi-efficiency LED LED low glare Highbay Luminaire, Body made of di-cast aluminium and hi-precision glass optics.

230 V with standard driver, CRI>70, CCT available in 3000K/4000K/5700K/6500K. Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| HB0903PFXXN120N000019065 | 120      | 60/90      | 180   555   240             | 18500     |
| HB0903PFXXN150N000019065 | 150      | 60/90      | 180   555   240             | 21250     |



IP65

## COB BAYSTORM -4 HB0904 (180 | 200W HIGHBAY)

Arraystorm COB BAYSTORM-4, Hi-efficiency LED LED low glare Highbay Luminaire, Body made of di-cast aluminium and hi-precision glass optics

230 V with standard driver, CRI>70, CCT available in 3000K/4000K/5700K/6500K. Driver also available in DALI | Analog

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| HB0904PFXXN180N000019065 | 180      | 60/90      | 370   370   240             | 26000     |
| HB0904PFXXN200N000019065 | 200      | 60/90      | 370   370   240             | 26750     |



IP65

## COB BAYSTORM -6 HB0906 (240 | 300W HIGHBAY)

Arraystorm COB BAYSTORM-6, Hi-efficiency LED LED low glare Highbay Luminaire, Body made of di-cast aluminium and hi-precision glass optics.

230 V with standard driver, CRI>70, CCT available in 3000K/4000K/5700K/6500K. Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| HB0906PFXXN240N000019065 | 240      | 60/90      | 555   365   240             | 39500     |
| HB0906PFXXN300N000019065 | 300      | 60/90      | 555   365   240             | 42000     |



IP65

## SMD MODULAR BAYSTORM -2 HB0932 (80 | 100W HIGHBAY)

Arraystorm SMD MODULAR BAYSTORM-2, Hi-efficiency LED Highbay Luminaire, Body made of high grade aluminium and hi-precision optics.

230 V with standard driver, CRI>70, CCT available in 3000K/4000K/5700K/6500K. Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| HB0932PFXXN080N00019065  | 80       | 30/60/90   | 327   218   177             | 10000     |
| HB0932PFXXN100N00019065  | 100      | 30/60/90   | 327   218   177             | 10250     |
| HIGH EFFICIENCY          |          |            |                             |           |
| HB0932PFXXN080N140019065 | 80       | 30/60/90   | 327   218   177             | 11500     |
| HB0932PFXXN100N140019065 | 100      | 30/60/90   | 327   218   177             | 12000     |



## SMD MODULAR BAYSTORM -3 HB0933 (120 | 150W HIGHBAY)

Arraystorm SMD MODULAR BAYSTORM-3, Hi-efficiency LED Highbay Luminaire, Body made of high grade aluminium and hi-precision optics.

230 V with standard driver,  
CRI>70,  
CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| HB0933PFXXN120N000019065 | 120      | 30/60/90   | 327   218   177             | 14000     |
| HB0933PFXXN150N000019065 | 150      | 30/60/90   | 327   218   177             | 15500     |
| HIGH EFFICIENCY          |          |            |                             |           |
| HB0933PFXXN120N140019065 | 120      | 30/60/90   | 327   218   177             | 16500     |
| HB0933PFXXN150N140019065 | 150      | 30/60/90   | 327   218   177             | 18000     |



## SMD MODULAR BAYSTORM -4 HB0934 (180 | 200W HIGHBAY)

Arraystorm SMD MODULAR BAYSTORM-4, Hi-efficiency LED Highbay Luminaire, Body made of high grade aluminium and hi-precision optics.

230 V with standard driver,  
CRI>70,  
CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| HB0934PFXXN180N000019065 | 180      | 30/60/90   | 624   212   177             | 20000     |
| HB0934PFXXN200N000019065 | 200      | 30/60/90   | 624   212   177             | 21000     |
| HIGH EFFICIENCY          |          |            |                             |           |
| HB0934PFXXN180N140019065 | 180      | 30/60/90   | 624   212   177             | 23250     |
| HB0934PFXXN200N140019065 | 200      | 30/60/90   | 624   212   177             | 23250     |

IP65



## SMD MODULAR BAYSTORM -6 HB0936 (240 | 300W HIGHBAY)

Arraystorm SMD MODULAR BAYSTORM-6, Hi-efficiency LED Highbay Luminaire, Body made of high grade aluminium and hi-precision optics

230 V with standard driver,  
CRI>70,  
CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| HB0936PFXXN240N000019065 | 240      | 30/60/90   | 924   218   177             | 35000     |
| HB0936PFXXN300N000019065 | 300      | 30/60/90   | 924   218   177             | 36500     |
| HIGH EFFICIENCY          |          |            |                             |           |
| HB0936PFXXN240N140019065 | 240      | 30/60/90   | 924   218   177             | 40750     |
| HB0936PFXXN300N140019065 | 300      | 30/60/90   | 924   218   177             | 41750     |

IP65



## SMD LINEAR BAYSTORM 1 HB0926 (40 | 50W LINEAR SMD HIGHBAY)

Arraystorm SMD LINEAR MODULAR BAYSTORM-1, Hi-efficiency LED Highbay Luminaire, Body made of high grade aluminium and hi-precision optics.

230 V with standard driver,  
CRI>70,  
CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| HB0926PFXXN040N000019065 | 40       | 30/60/90   | 324   98   177              | 5500      |
| HB0926PFXXN050N000019065 | 50       | 30/60/90   | 324   98   177              | 6000      |
| HIGH EFFICIENCY          |          |            |                             |           |
| HB0926PFXXN040N140019065 | 40       | 30/60/90   | 324   98   177              | 6250      |
| HB0926PFXXN050N140019065 | 50       | 30/60/90   | 324   98   177              | 6500      |

IP65



## SMD LINEAR BAYSTORM HB0927 (80 | 100W LINEAR SMD HIGHBAY)

Arraystorm SMD LINEAR MODULAR BAYSTORM-2, Hi-efficiency LED Highbay Luminaire, Body made of high grade aluminium and hi-precision optics.

230 V with standard driver,  
CRI>70,  
CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| HB0927PFXXN080N000019065 | 80       | 30/60/90   | 624   98   177              | 10500     |
| HB0927PFXXN100N000019065 | 100      | 30/60/90   | 624   98   177              | 10500     |
| HIGH EFFICIENCY          |          |            |                             |           |
| HB0927PFXXN080N140019065 | 80       | 30/60/90   | 624   98   177              | 12250     |
| HB0927PFXXN100N140019065 | 100      | 30/60/90   | 624   98   177              | 12250     |

IP65



## SMD LINEAR BAYSTORM HB0928 (120 | 150W LINEAR SMD HIGHBAY)

Arraystorm SMD LINEAR MODULAR BAYSTORM-3, Hi-efficiency LED Highbay Luminaire, Body made of high grade aluminium and hi-precision optics.

230 V with standard driver,  
CRI>70,  
CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| HB0928PFXXN120N000019065 | 120      | 30/60/90   | 924   98   177              | 14000     |
| HB0928PFXXN150N000019065 | 150      | 30/60/90   | 924   98   177              | 15500     |
| HIGH EFFICIENCY          |          |            |                             |           |
| HB0928PFXXN120N140019065 | 120      | 30/60/90   | 924   98   177              | 16500     |
| HB0928PFXXN150N140019065 | 150      | 30/60/90   | 924   98   177              | 18000     |

IP65



## SMD LINEAR BAYSTORM HB0929 (200W LINEAR SMD HIGHBAY)

Arraystorm SMD LINEAR MODULAR BAYSTORM-4, Hi-efficiency LED Highbay Luminaire, Body made of high grade aluminium and hi-precision optics

230 V with standard driver,  
CRI>70,  
CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| HB0929PFXXN200N000019065 | 200      | 30/60/90   | 1224   98   177             | 20900     |
| HB0929PFXXN200N140019065 | 200      | 30/60/90   | 1224   98   177             | 23750     |



## UFO BAYSTORM HB0941/HB0942/HB0943 (80|100|120|180|200W SMD UFO HIGHBAY)

Arraystorm UFO SMD BAYSTORM 2, Hi-efficiency LED Highbay Luminaire, Body made of di-cast aluminium and hi-precision optics.

230 V with standard driver,  
CRI>70,  
CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| HB0941PFXXN080N120019065 | 80       | 90/120     | 230   185                   | 9000      |
| HB0941PFXXN100N120019065 | 100      | 90/120     | 230   185                   | 9250      |
| HB0942PFXXN120N120019065 | 120      | 90/120     | 300   185                   | 13500     |
| HB0942PFXXN150N120019065 | 150      | 90/120     | 300   185                   | 15500     |
| HB0943PFXXN180N120019065 | 180      | 90/120     | 330   190                   | 19000     |
| HB0943PFXXN200N120019065 | 200      | 90/120     | 330   190                   | 19000     |



## UFO HIGH EFFICIENCY BAYSTORM HB0941HE/HB0942HE/HB0943HE (80|100|120|180|200W SMD UFO HIGHBAY)

Arraystorm UFO SMD BAYSTORM 2, Hi-efficiency LED Highbay Luminaire, Body made of di-cast aluminium and hi-precision optics.

230 V with standard driver,  
CRI>70,  
CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| HB0941PFXXN080N150019065 | 80       | 90/120     | 230   185                   | 10250     |
| HB0941PFXXN100N150019065 | 100      | 90/120     | 230   185                   | 10500     |
| HB0942PFXXN120N150019065 | 120      | 90/120     | 300   185                   | 16000     |
| HB0942PFXXN150N150019065 | 150      | 90/120     | 300   185                   | 17500     |
| HB0943PFXXN180N150019065 | 180      | 90/120     | 330   190                   | 22000     |
| HB0943PFXXN200N150019065 | 200      | 90/120     | 330   190                   | 22000     |



IP40

## INDUSTRIAL SABER IP40 BT9003 (BATTEN)

Hi-efficiency Industrial Saber LED Batten Luminaire, Body made of extruded aluminium housing & polycarbonate opal finish.

230 V with standard driver, CRI>80,  
IP40CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| BT9003SFXXN020N2FS000000 | 20       | 140        | 592   56   74.5             | 3000      |
| BT9003SFXXN040N4FS000000 | 40       | 140        | 1192   56   74.5            | 4500      |



IP40

## MAXIM INDUSTRIAL TRUNKING TK9008

Arraystorm Maxim Industrial Trunking TK9008 System,  
Body made of extruded aluminium housing.

can accommodate upto 9 wires for single phase / 3 phase / Emergency as well as dimming wires along with snap fitting trunk Light, Cover, End Caps and suspension

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| TK9008SFXXNXXXN1MT000000 | NA       | NA         | 1000   56   58              | 1600      |
| TK9009XXXXXCOVX1MT000000 | NA       | NA         | 1000   56   10              | 525       |
| BT9003SFXXN020N2FS00WC00 | 20       | 140        | 592   56   34.5             | 2250      |
| BT9003SFXXN040N4FS00WC00 | 40       | 140        | 1192   56   34.5            | 4000      |



## MAXIM COMMERCIAL TRUNKING TK9006

Arraystorm Maxim commercial Trunking TK9006 System,  
Body made of extruded aluminium housing.

can accommodate upto 9 wires for single phase / 3 phase / Emergency as well as dimming wires along with snap fitting trunk Light, Cover, End Caps and suspension.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| TK9006SFXXXXXXX1MTXXXXXX | NA       | NA         | 1000   56   58              | 1150      |
| TK9007XXXXXCOVX1MT000000 | NA       | NA         | 1000   56   10              | 375       |
| BT9002SFXXN020N4FS000000 | 20       | 140        | 1200   30   35              | 1050      |
| BT9004SFXXN040N4FS000000 | 40       | 140        | 1200   42   48              | 1750      |

IP65

## INDUSTRIAL SABER IP65 (BATTEN IP65)

Body made of co-extruded polycarbonate. 230 V with standard driver,

CRI>80, CCT available in 3000K/4000K/5700K/6500K.

Driver also available in DALI | Analog

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| BT9005SFXXN020N2FS000000 | 20       | 140        | 600   53   74               | 2500      |
| BT9005SFXXN040N4FS000000 | 40       | 140        | 1200   53   74              | 3750      |

IP65

## BAYSTAR -1 WG1911/WG1912 (WELL GLASS )

Hi-efficiency LED Wellglass Luminaire,  
Body made of di-cast aluminium housing.

230 V with standard driver, CRI>70,  
CCT available in 3000K/4000K/5700K/6500K.

Driver also available in DALI | Analog

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|-----------------------------|-----------|
| WG1911PFXXN030N000020000T | 30       | 140        | 119   106                   | 3000      |
| WG1911PFXXN040N000020000T | 40       | 140        | 119   106                   | 3500      |
| WG1912PFXXN060N000020000T | 60       | 140        | 175   165                   | 6500      |
| WG1912PFXXN070N000020000T | 70       | 140        | 175   165                   | 7250      |
| WG1912PFXXN080N000020000T | 80       | 140        | 175   165                   | 7500      |

IP54

## BAYSTAR-2 (BULK HEAD)

Hi-efficiency LED Bulkhead Luminaire, Body and diffuser made of Polycarbonate housing. 230 V with standard driver,

230 V with standard driver,  
CRI>80, CCT available in 3000K/4000K/5700K/6500K.

Driver also available in DALI | Analog

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|-----------------------------|-----------|
| BK0921FFXXN009N000000000T | 9        | 120        | 212   82   70               | 2000      |



The background of the entire page is a photograph of a large, modern indoor sports hall. The hall has a high ceiling with a series of large, multi-paned windows that let in natural light. The floor is a bright green synthetic material with white and blue lines marking out a sports court. In the background, a volleyball net is visible. Overlaid on the image are several large, semi-transparent orange geometric shapes, primarily triangles and trapezoids, which create a dynamic, modern feel. A central orange rectangle contains the title text.

# FLOODLIGHT

# SMD Floodstorm (Flood Light)

Hi-efficiency LED Highbay Luminaire, Body made of di-cast aluminium.

230 V with standard driver, CRI>70,

CCT available in 3000K/4000K/5700K/6500K. Driver also available in DALI | Analog



| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|-----------------------------|-----------|
| FL0702PMXXN020N000010065T | 20       | 120        | 163   160   45              | 3100      |
| FL0703PMXXN030N000010065T | 30       | 120        | 200   180   60              | 4400      |
| FL0704PMXXN050N000010065T | 50       | 120        | 215   210   60              | 5300      |
| FL0705PMXXN072N000010065T | 72       | 120        | 270   245   70              | 6700      |
| FL0705PMXXN100N000010065T | 100      | 120        | 270   245   70              | 8800      |
| FL0706PMXXN120N000010065T | 120      | 120        | 305   285   80              | 9800      |
| FL0706PMXXN150N000010065T | 150      | 120        | 305   285   80              | 11500     |
| FL0707PMXXN200N000010065T | 200      | 120        | 345   325   80              | 16500     |
| FL0707PMXXN250N000010065T | 250      | 120        | 345   325   80              | 17000     |



## FLOODSTORM FL0710 (450W FLOOD LIGHT)

Hi-efficiency LED Highbay Luminaire, Body made of di-cast aluminium.

230 V with standard driver, CRI>70,

CCT available in 3000K/4000K/5700K/6500K.

Driver also available in DALI | Analog

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| FL0710PMXXN450N140013065 | 450      | 30/60/90   | 605   405   260             | 53000     |

IP65



## FLOODSTORM -1 FL0901 (40 | 50W FLOOD LIGHT)

Arraystorm Hi-efficiency LED low glare COB Floodlight Luminaire, Body made of di-cast aluminium and hi-precision glass optics.

230 V with standard driver, CRI>70,  
CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| FL0901PMXXN040N000019065 | 40       | 60   90    | 180   180   340             | 6750      |
| FL0901PMXXN050N000019065 | 50       | 60   90    | 180   180   340             | 7000      |

IP65



## FLOODSTORM -2 FL0902 (80 | 100W FLOOD LIGHT)

Arraystorm Hi-efficiency LED low glare COB Floodlight Luminaire, Body made of di-cast aluminium and hi-precision glass optics.

230 V with standard driver, CRI>70,  
CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| FL0902PMXXN080N000019065 | 80       | 60   90    | 180   365   200             | 13000     |
| FL0902PMXXN100N000019065 | 100      | 60   90    | 180   365   200             | 13500     |

IP65



## FLOODSTORM -3 FL0903 (120 | 150W FLOOD LIGHT)

Arraystorm Hi-efficiency LED low glare COB Floodlight Luminaire, Body made of di-cast aluminium and hi-precision glass optics.

230 V with standard driver, CRI>70,  
CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| FL0903PMXXN120N000019065 | 120      | 60   90    | 412   412   340             | 18750     |
| FL0903PMXXN150N000019065 | 150      | 60   90    | 412   412   340             | 21500     |



## FLOODSTORM -4 FL0904 ( 180 | 200W FLOOD LIGHT)

Arraystorm Hi-efficiency LED low glare COB Floodlight Luminaire, Body made of di-cast aluminium and hi-precision glass optics.

230 V with standard driver, CRI>70,  
CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| FL0904PMXXN180N000019065 | 180      | 60   90    | 385   385   200             | 26750     |
| FL0904PMXXN200N000019065 | 200      | 60   90    | 385   385   200             | 27500     |



## FLOODSTORM -6 FL0906 ( 240 | 300W FLOOD LIGHT)

Arraystorm Hi-efficiency LED low glare COB Floodlight Luminaire, Body made of di-cast aluminium and hi-precision glass optics.

230 V with standard driver, CRI>70,  
CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|-----------------------------|-----------|
| FL0906PMXXN240N000019065 | 240      | 60   90    | 385   570   200             | 41500     |
| FL0906PMXXN300N000019065 | 300      | 60   90    | 385   570   200             | 42750     |

IP65



## SMD MODULAR FLOODSTORM -1 FL0926 (40 | 50W MODULAR SMD FLOODLIGHT)

Hi-efficiency LED Highbay Luminaire, Body made of di-cast aluminium.

230 V with standard driver, CRI>70,  
CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE   | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|--------------|-----------------------------|-----------|
| FL0926PMXXN040N140019065 | 40       | 30   60   90 | 324   98   177              | 6750      |
| FL0926PMXXN050N140019065 | 50       | 30   60   90 | 324   98   177              | 7000      |

IP65



## SMD MODULAR FLOODSTORM -2 FL0932 (80 | 100W MODULAR SMD FLOODLIGHT)

Hi-efficiency LED Highbay Luminaire, Body made of di-cast aluminium.

230 V with standard driver, CRI>70,  
CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE   | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|--------------|-----------------------------|-----------|
| FL0932PMXXN080N140019065 | 80       | 30   60   90 | 327   218   177             | 13000     |
| FL0932PMXXN100N140019065 | 100      | 30   60   90 | 327   218   177             | 13250     |

IP65



## SMD MODULAR FLOODSTORM -3 FL0933 (120 | 150W MODULAR SMD FLOODLIGHT)

Hi-efficiency LED Highbay Luminaire, Body made of di-cast aluminium.

230 V with standard driver, CRI>70,  
CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE   | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|--------------|-----------------------------|-----------|
| FL0933PMXXN120N140019065 | 120      | 30   60   90 | 327   218   177             | 16750     |
| FL0933PMXXN150N140019065 | 150      | 30   60   90 | 327   218   177             | 18250     |



## SMD MODULAR FLOODSTORM -4 FL0934 (180 | 200W MODULAR SMD FLOODLIGHT)

Hi-efficiency LED Highbay Luminaire, Body made of di-cast aluminium.

230 V with standard driver, CRI>70,  
CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE   | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|--------------|-----------------------------|-----------|
| FL0934PMXXN180N140019065 | 180      | 30   60   90 | 624   225   177             | 23500     |
| FL0934PMXXN200N140019065 | 200      | 30   60   90 | 624   225   177             | 23500     |



## SMD MODULAR FLOODSTORM -6 FL0936 (240 | 300W MODULAR SMD HIGHBAY)

Hi-efficiency LED Highbay Luminaire, Body made of di-cast aluminium.

230 V with standard driver, CRI>70,  
CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE   | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|--------------|-----------------------------|-----------|
| FL0936PMXXN240N140019065 | 240      | 30   60   90 | 924   225   177             | 40500     |
| FL0936PMXXN300N140019065 | 300      | 30   60   90 | 924   225   177             | 42500     |

# SMT LINE

PICK & PLACE MACHINE

JUKI

JX-350

00035



A nighttime photograph of a city street featuring a bridge with light trails from moving vehicles. Several streetlights are visible, casting a warm glow. The image is overlaid with diagonal orange and dark grey geometric shapes. A central orange rectangle contains the title text.

# STREETLIGHT



**Arraystorm™**  
Sense the future

IP65



## OPTIMUS-1 (STREET LIGHT)

Hi-efficient LED Streetlight, Housing made of die-cast aluminium, with street optic LENS for uniform light distribution. Rated IP66

230 V with standard driver, CRI>70,  
CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog.



| PRODUCT CODE              | WATT (W) | BEAM ANGLE          | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|---------------------|-----------------------------|-----------|
| ST0801PFXXN018N000020065T | 18       | Street Light Optics | 280   105   55              | 2850      |
| ST0801PFXXN024N000020065T | 24       | Street Light Optics | 280   105   55              | 3350      |
| ST0802PFXXN036N000020065T | 36       | Street Light Optics | 340   130   55              | 3600      |
| ST0803PFXXN050N000020065T | 50       | Street Light Optics | 395   160   55              | 5750      |
| ST0803PFXXN072N000020065T | 72       | Street Light Optics | 395   160   55              | 6200      |
| ST0804PFXXN100N000020065T | 100      | Street Light Optics | 480   190   70              | 9200      |
| ST0805PFXXN120N000020065T | 120      | Street Light Optics | 570   205   70              | 9700      |
| ST0805PFXXN150N000020065T | 150      | Street Light Optics | 570   205   70              | 11500     |

IP65



## OPTIMUS-2 ST0822 (50W HIGH PERFORMANCE STREET LIGHT)

Hi-efficient LED Streetlight, Housing made of die-cast aluminium, with street optic LENS for uniform light distribution. Rated IP66

230 V with standard driver, CRI>70,  
CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE          | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|---------------------|-----------------------------|-----------|
| ST0822PFXXN050N120020065 | 50       | Street Light Optics | 360   160   180             | 6750      |
| ST0822PFXXN050N140020065 | 50       | Street Light Optics | 360   160   180             | 8000      |



## OPTIMUS-3 ST0823 (80 | 100W HIGH PERFORMANCE STREET LIGHT)

High performance and HI-efficient LED Streetlight, Housing made of die-cast aluminium, with street optic LENS for uniform light distribution. Rated IP66

230 V with standard driver, CRI>70,  
CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE          | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|---------------------|-----------------------------|-----------|
| ST0823PFXXN080N120020065 | 80       | Street Light Optics | 430   200   115             | 10750     |
| ST0823PFXXN100N120020065 | 100      | Street Light Optics | 430   200   115             | 12000     |
| HIGH EFFICIENCY          |          |                     |                             |           |
| ST0823PFXXN080N140020065 | 80       | Street Light Optics | 430   200   115             | 11750     |
| ST0823PFXXN100N140020065 | 100      | Street Light Optics | 430   200   115             | 13750     |



## OPTIMUS-4 ST0824 (120 | 150W HIGH PERFORMANCE STREET LIGHT)

High performance and HI-efficient LED Streetlight, Housing made of die-cast aluminium, with street optic LENS for uniform light distribution. Rated IP66

230 V with standard driver, CRI>70,  
CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE          | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|---------------------|-----------------------------|-----------|
| ST0824PFXXN120N120020065 | 120      | Street Light Optics | 470   270   85              | 12500     |
| ST0824PFXXN150N120020065 | 150      | Street Light Optics | 470   270   85              | 15000     |
| HIGH EFFICIENCY          |          |                     |                             |           |
| ST0824PFXXN120N140020065 | 120      | Street Light Optics | 472   270   85              | 14500     |
| ST0824PFXXN150N140020065 | 150      | Street Light Optics | 472   270   85              | 17750     |



## OPTIMUS-5 ST0825 (200 | 240W HIGH PERFORMANCE STREET LIGHT)

High performance and HI-efficient LED Streetlight, Housing made of die-cast aluminium, with street optic LENS for uniform light distribution. Rated IP66

230 V with standard driver, CRI>70,  
CCT available in 3000K/4000K/5700K/6500K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE          | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|---------------------|-----------------------------|-----------|
| ST0825PFXXN200N120020065 | 200      | Street Light Optics | 555   265   80              | 21000     |
| ST0825PFXXN240N120020065 | 240      | Street Light Optics | 555   265   80              | 23000     |
| HIGH EFFICIENCY          |          |                     |                             |           |
| ST0825PFXXN200N140020065 | 200      | Street Light Optics | 555   265   80              | 24000     |
| ST0825PFXXN240N140020065 | 240      | Street Light Optics | 555   265   80              | 27500     |



A photograph of a cleanroom environment. In the background, two workers wearing white protective suits and hairnets are visible. The foreground features industrial machinery, including a large green roller and a silver cylindrical component. The floor is highly reflective. The image is overlaid with large, diagonal orange shapes.

# CLEANROOM



IP65

## EPIC CLEANROOM CR2050 (BOCR 1X1 PC | 1X1 SS)

Arraystorm EPIC Bottom Opening Clean Room (BOCR) Recessed High Efficiency Cleanroom LED Gridlight, Body made of CRCA, Frame made of powder coated CRCA or Stainless Steel and Polycarbonate Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | CUTOUT (mm) L   W | DIMENSION (mm) L   W   H | MRP (INR) |
|---------------------------|----------|------------|-------------------|--------------------------|-----------|
| CR2050RFXXN018N0000000BO  | 18       | 120        | 325   325         | 340   340   69           | 8750      |
| CR2050RFXXN018N000000SSBO | 18       | 120        | 325   325         | 340   340   69           | 9750      |



IP65

## EPIC CLEANROOM CR2051 (BOCR 2X2 PC)

Arraystorm EPIC Bottom Opening Clean Room (BOCR) Recessed High Efficiency Cleanroom LED Gridlight, Body made of CRCA, Frame made of powder coated CRCA or Stainless Steel and Polycarbonate Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog  
Driver also available in DALI | Analog | White color tunable.  
For POP | Gypsum ceiling, frame to be ordered separately.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | CUTOUT (mm) L   W | DIMENSION (mm) L   W   H | MRP (INR) |
|--------------------------|----------|------------|-------------------|--------------------------|-----------|
| CR2051RFXXN032N0000000BO | 32       | 120        | 600   600         | 630   630   75           | 13000     |
| CR2051RFXXN042N0000000BO | 42       | 120        | 600   600         | 630   630   75           | 14000     |
| CR2051RFXXN060N0000000BO | 60       | 120        | 600   600         | 630   630   75           | 15500     |
| CR2051RFXXN080N0000000BO | 80       | 120        | 600   600         | 630   630   75           | 17750     |



IP65

## EPIC CLEANROOM CR2051 (BOCR 2X2 SS)

Arraystorm EPIC Bottom Opening Clean Room (BOCR) Recessed High Efficiency Cleanroom LED Gridlight, Body made of CRCA, Frame made of powder coated CRCA or Stainless Steel and Polycarbonate Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | CUTOUT (mm) L   W | DIMENSION (mm) L   W   H | MRP (INR) |
|---------------------------|----------|------------|-------------------|--------------------------|-----------|
| CR2051RFXXN032N000000SSBO | 32       | 120        | 600   600         | 630   630   75           | 14000     |
| CR2051RFXXN042N000000SSBO | 42       | 120        | 600   600         | 630   630   75           | 15000     |
| CR2051RFXXN060N000000SSBO | 60       | 120        | 600   600         | 630   630   75           | 16500     |
| CR2051RFXXN080N000000SSBO | 80       | 120        | 600   600         | 630   630   75           | 18750     |



IP65

## EPIC CLEANROOM CR2052 (BOCR 1X2 PC)

Arraystorm EPIC Bottom Opening Clean Room (BOCR) Recessed High Efficiency Cleanroom LED Gridlight, Body made of CRCA, Frame made of powder coated CRCA or Stainless Steel and Polycarbonate Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | CUTOUT (mm) L   W | DIMENSION (mm) L   W   H | MRP (INR) |
|--------------------------|----------|------------|-------------------|--------------------------|-----------|
| CR2052RFXXN032N0000000BO | 32       | 120        | 600   300         | 630   330   75           | 12500     |
| CR2052RFXXN042N0000000BO | 42       | 120        | 600   300         | 630   330   75           | 13500     |



IP65

## EPIC CLEANROOM CR2052 (BOCR 1X2 SS)

Arraystorm EPIC Bottom Opening Clean Room (BOCR) Recessed High Efficiency Cleanroom LED Gridlight, Body made of CRCA, Frame made of powder coated CRCA or Stainless Steel and Polycarbonate Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | CUTOUT (mm) L   W | DIMENSION (mm) L   W   H | MRP (INR) |
|---------------------------|----------|------------|-------------------|--------------------------|-----------|
| CR2052RFXXN032N000000SSBO | 32       | 120        | 600   300         | 630   330   75           | 15000     |
| CR2052RFXXN042N000000SSBO | 42       | 120        | 600   300         | 630   330   75           | 16000     |



IP65

## EPIC CLEANROOM CR2053 (BOCR 1X4 PC)

Arraystorm EPIC Bottom Opening Clean Room (BOCR) Recessed High Efficiency Cleanroom LED Gridlight, Body made of CRCA, Frame made of powder coated CRCA or Stainless Steel and Polycarbonate Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | CUTOUT (mm) L   W | DIMENSION (mm) L   W   H | MRP (INR) |
|--------------------------|----------|------------|-------------------|--------------------------|-----------|
| CR2053RFXXN032N0000000BO | 32       | 120        | 1200   300        | 1230   330   75          | 14000     |
| CR2053RFXXN042N0000000BO | 42       | 120        | 1200   300        | 1230   330   75          | 15000     |
| CR2053RFXXN060N0000000BO | 60       | 120        | 1200   300        | 1230   330   75          | 16500     |
| CR2053RFXXN080N0000000BO | 80       | 120        | 1200   300        | 1230   330   75          | 18750     |

IP65



## EPIC CLEANROOM CR2053 (BOCR 1X4 SS)

Arraystorm EPIC Bottom Opening Clean Room (BOCR) Recessed High Efficiency Cleanroom LED Gridlight, Body made of CRCA, Frame made of powder coated CRCA or Stainless Steel and Polycarbonate Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|----------------------|-----------------------------|-----------|
| CR2053RFXXN032N00000SSBO | 32       | 120        | 1200   300           | 1230   330   75             | 15500     |
| CR2053RFXXN042N00000SSBO | 42       | 120        | 1200   300           | 1230   330   75             | 16500     |
| CR2053RFXXN060N00000SSBO | 60       | 120        | 1200   300           | 1230   330   75             | 17750     |
| CR2053RFXXN080N00000SSBO | 80       | 120        | 1200   300           | 1230   330   75             | 20500     |

IP65




## EPIC CLEANROOM CR2054 (BOCR 2X4 PC)

Arraystorm EPIC Bottom Opening Clean Room (BOCR) Recessed High Efficiency Cleanroom LED Gridlight, Body made of CRCA, Frame made of powder coated CRCA or Stainless Steel and Polycarbonate Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|----------------------|-----------------------------|-----------|
| CR2054RFXXN060N0000000BO | 60       | 120        | 1200   600           | 1230   630   75             | 27500     |
| CR2054RFXXN080N0000000BO | 80       | 120        | 1200   600           | 1230   630   75             | 29500     |
| CR2054RFXXN100N0000000BO | 100      | 120        | 1200   600           | 1230   630   75             | 32000     |
| CR2054RFXXN120N0000000BO | 120      | 120        | 1200   600           | 1230   630   75             | 36750     |
| CR2054RFXXN140N0000000BO | 140      | 120        | 1200   600           | 1230   630   75             | 38250     |

IP65



## EPIC CLEANROOM CR2054 (BOCR 2X4 SS)

Arraystorm EPIC Bottom Opening Clean Room (BOCR) Recessed High efficiency Cleanroom LED Gridlight, Body made of CRCA, Frame made of powder coated CRCA or Stainless Steel and Polycarbonate Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|----------------------|-----------------------------|-----------|
| CR2054RFXXN060N00000SSBO | 60       | 120        | 1200   600           | 1230   630   75             | 29750     |
| CR2054RFXXN080N00000SSBO | 80       | 120        | 1200   600           | 1230   630   75             | 31850     |
| CR2054RFXXN100N00000SSBO | 100      | 120        | 1200   600           | 1230   630   75             | 34500     |
| CR2054RFXXN120N00000SSBO | 120      | 120        | 1200   600           | 1230   630   75             | 39250     |
| CR2054RFXXN140N00000SSBO | 140      | 120        | 1200   600           | 1230   630   75             | 40750     |



IP65

## EPIC CLEANROOM CR2056 (SCREWLESS BOCR 2X2 PC)

Arraystorm EPIC Bottom Opening Clean Room (BOCR) Recessed High Efficiency Cleanroom LED Gridlight, Body made of CRCA, Frame made of powder coated CRCA or Stainless Steel and Polycarbonate Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|----------------------|-----------------------------|-----------|
| CR2056RFXXN032N0000000BO | 32       | 120        | 600   600            | 630   630   75              | 13000     |
| CR2056RFXXN042N0000000BO | 42       | 120        | 600   600            | 630   630   75              | 14000     |
| CR2056RFXXN060N0000000BO | 60       | 120        | 600   600            | 630   630   75              | 15500     |
| CR2056RFXXN080N0000000BO | 80       | 120        | 600   600            | 630   630   75              | 17750     |



IP65

## EPIC CLEANROOM CR2060 (TOCR 1X1 PC | SS)

Arraystorm EPIC Top Opening Clean Room (TOCR) Recessed High Efficiency Cleanroom LED Gridlight, Body made of CRCA, Frame made of powder coated CRCA or Stainless Steel and Polycarbonate Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver,  
CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog

| PRODUCT CODE               | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|----------------------------|----------|------------|----------------------|-----------------------------|-----------|
| CR2060RFXXN018N0000000TO   | 18       | 120        | 300   300            | 340   340   136             | 7750      |
| CR2060RFXXN018N0000000SSTO | 18       | 120        | 300   300            | 340   340   136             | 8750      |



IP65

## EPIC CLEANROOM CR2061 (TOCR 2X2 PC)

Arraystorm EPIC Top Opening Clean Room (TOCR) Recessed High Efficiency Cleanroom LED Gridlight, Body made of CRCA, Frame made of powder coated CRCA or Stainless Steel and Polycarbonate Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|----------------------|-----------------------------|-----------|
| CR2061RFXXN032N0000000TO | 32       | 120        | 600   600            | 640   640   136             | 12000     |
| CR2061RFXXN042N0000000TO | 42       | 120        | 600   600            | 640   640   136             | 13000     |
| CR2061RFXXN060N0000000TO | 60       | 120        | 600   600            | 640   640   136             | 14500     |
| CR2061RFXXN080N0000000TO | 80       | 120        | 600   600            | 640   640   136             | 16750     |



IP65

## EPIC CLEANROOM CR2061 (TOCR 2X2 SS)

Arraystorm EPIC Top Opening Clean Room (TOCR) Recessed High Efficiency Cleanroom LED Gridlight, Body made of CRCA, Frame made of powder coated CRCA or Stainless Steel and Polycarbonate Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | CUTOUT (mm) L   W | DIMENSION (mm) L   W   H | MRP (INR) |
|--------------------------|----------|------------|-------------------|--------------------------|-----------|
| CR2061RFXXN032N00000SSTO | 32       | 120        | 600   600         | 640   640   136          | 13000     |
| CR2061RFXXN042N00000SSTO | 42       | 120        | 600   600         | 640   640   136          | 14000     |
| CR2061RFXXN060N00000SSTO | 60       | 120        | 600   600         | 640   640   136          | 15500     |
| CR2061RFXXN080N00000SSTO | 80       | 120        | 600   600         | 640   640   136          | 17750     |



IP65

## EPIC CLEANROOM CR2062 (TOCR 1X2 PC)

Arraystorm EPIC Top Opening Clean Room (TOCR) Recessed High Efficiency Cleanroom LED Gridlight, Body made of CRCA, Frame made of powder coated CRCA or Stainless Steel and Polycarbonate Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | CUTOUT (mm) L   W | DIMENSION (mm) L   W   H | MRP (INR) |
|--------------------------|----------|------------|-------------------|--------------------------|-----------|
| CR2062RFXXN032N0000000TO | 32       | 120        | 600   300         | 640   340   136          | 11500     |
| CR2062RFXXN042N0000000TO | 42       | 120        | 600   300         | 640   340   136          | 12500     |



IP65

## EPIC CLEANROOM CR2062 (TOCR 1X2 SS)

Arraystorm EPIC Top Opening Clean Room (TOCR) Recessed High Efficiency Cleanroom LED Gridlight, Body made of CRCA, Frame made of powder coated CRCA or Stainless Steel and Polycarbonate Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | CUTOUT (mm) L   W | DIMENSION (mm) L   W   H | MRP (INR) |
|--------------------------|----------|------------|-------------------|--------------------------|-----------|
| CR2062RFXXN032N00000SSTO | 32       | 120        | 600   300         | 640   340   136          | 14000     |
| CR2062RFXXN042N00000SSTO | 42       | 120        | 600   300         | 640   340   136          | 15000     |

IP65



## EPIC CLEANROOM CR2063 (TOCR 1X4 PC)

Arraystorm EPIC Top Opening Clean Room (TOCR) Recessed High Efficiency Cleanroom LED Gridlight, Body made of CRCA, Frame made of powder coated CRCA or Stainless Steel and Polycarbonate Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|----------------------|-----------------------------|-----------|
| CR2063RFXXN032N0000000TO | 32       | 120        | 1200   300           | 1240   340   136            | 13000     |
| CR2063RFXXN042N0000000TO | 42       | 120        | 1200   300           | 1240   340   136            | 14000     |
| CR2063RFXXN060N0000000TO | 60       | 120        | 1200   300           | 1240   340   136            | 15500     |
| CR2063RFXXN080N0000000TO | 80       | 120        | 1200   300           | 1240   340   136            | 17750     |

IP65



## EPIC CLEANROOM CR2063 (TOCR 1X4 SS)

Arraystorm EPIC Top Opening Clean Room (TOCR) Recessed High Efficiency Cleanroom LED Gridlight, Body made of CRCA, Frame made of powder coated CRCA or Stainless Steel and Polycarbonate Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|----------------------|-----------------------------|-----------|
| CR2063RFXXN032N000000SSTO | 32       | 120        | 1200   300           | 1240   340   136            | 14500     |
| CR2063RFXXN042N000000SSTO | 42       | 120        | 1200   300           | 1240   340   136            | 15500     |
| CR2063RFXXN060N000000SSTO | 60       | 120        | 1200   300           | 1240   340   136            | 16750     |
| CR2063RFXXN080N000000SSTO | 80       | 120        | 1200   300           | 1240   340   136            | 19250     |

IP65



## EPIC CLEANROOM CR2064 (TOCR 2X4 PC)

Arraystorm EPIC Top Opening Clean Room (TOCR) Recessed High Efficiency Cleanroom LED Gridlight, Body made of CRCA, Frame made of powder coated CRCA or Stainless Steel and Polycarbonate Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|----------------------|-----------------------------|-----------|
| CR2064RFXXN060N0000000TO | 60       | 120        | 1200   600           | 1240   640   136            | 26250     |
| CR2064RFXXN080N0000000TO | 80       | 120        | 1200   600           | 1240   640   136            | 28250     |
| CR2064RFXXN100N0000000TO | 100      | 120        | 1200   600           | 1240   640   136            | 31250     |
| CR2064RFXXN120N0000000TO | 120      | 120        | 1200   600           | 1240   640   136            | 35000     |
| CR2064RFXXN140N0000000TO | 140      | 120        | 1200   600           | 1240   640   136            | 37500     |



## EPIC CLEANROOM CR2064 (TOCR 2X4 SS)

Arraystorm EPIC Top Opening Clean Room (TOCR) Recessed High Efficiency Cleanroom LED Gridlight, Body made of CRCA, Frame made of powder coated CRCA or Stainless Steel and Polycarbonate Diffuser with homogeneous light distribution without hotspots.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog

| PRODUCT CODE             | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|--------------------------|----------|------------|----------------------|-----------------------------|-----------|
| CR2064RFXXN060N00000SSTO | 60       | 120        | 1200   600           | 1240   640   136            | 28750     |
| CR2064RFXXN080N00000SSTO | 80       | 120        | 1200   600           | 1240   640   136            | 30750     |
| CR2064RFXXN100N00000SSTO | 100      | 120        | 1200   600           | 1240   640   136            | 33500     |
| CR2064RFXXN120N00000SSTO | 120      | 120        | 1200   600           | 1240   640   136            | 37500     |
| CR2064RFXXN140N00000SSTO | 140      | 120        | 1200   600           | 1240   640   136            | 39000     |



## EPIC CLEANROOM TOCR BUND COVER

Arraystorm EPIC TOCR Bund cover, Body made of powder coated CRCA.

| PRODUCT CODE               | Description   | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|----------------------------|---------------|-----------------------------|-----------|
| BC2071FFXXXXXXXXX1X10000TO | Cover for 1x1 | 350   350   85              | 2750      |
| BC2072FFXXXXXXXXX2X20000TO | Cover for 2x2 | 650   650   85              | 3750      |
| BC2073FFXXXXXXXXX1X20000TO | Cover for 1x2 | 650   350   85              | 3250      |
| BC2074FFXXXXXXXXX1X40000TO | Cover for 1X4 | 1250   350   85             | 3750      |
| BC2075FFXXXXXXXXX2X40000TO | Cover for 2x4 | 1250   650   85             | 6000      |







**FLAMEPROOF**



## FLAME PROOF CLEANROOM 1X1- PC CR2080

Arraystorm EPIC Flame Proof Recessed High Efficiency Cleanroom LED Gridlight, Body made of die cast Aluminium and Frame made of powder coated CRCA and high precision glass lens.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | CUTOUT (mm) L   W | DIMENSION (mm) L   W   H | MRP (INR) |
|---------------------------|----------|------------|-------------------|--------------------------|-----------|
| CR2080RFXXN030N00000FL00T | 30       | 120        | 275   275         | 312   312   140          | 20500     |
| CR2080RFXXN040N00000FL00T | 40       | 120        | 275   275         | 312   312   140          | 20500     |
| CR2080RFXXN050N00000FL00T | 50       | 120        | 275   275         | 312   312   140          | 20500     |



## FLAME PROOF CLEANROOM 1X1-SS CR2080

Arraystorm EPIC Flame Proof Recessed High Efficiency Cleanroom LED Gridlight, Body made of die cast Aluminium and Frame made of SS and high precision glass lens.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE               | WATT (W) | BEAM ANGLE | CUTOUT (mm) L   W | DIMENSION (mm) L   W   H | MRP (INR) |
|----------------------------|----------|------------|-------------------|--------------------------|-----------|
| CR2080RFXXN030N0000SSFL00T | 30       | 120        | 275   275         | 312   312   140          | 19500     |
| CR2080RFXXN040N0000SSFL00T | 40       | 120        | 275   275         | 312   312   140          | 20500     |
| CR2080RFXXN050N0000SSFL00T | 50       | 120        | 275   275         | 312   312   140          | 20750     |



## FLAME PROOF CLEANROOM -2X2 PC CR2081

Arraystorm EPIC Flame Proof Recessed High Efficiency Cleanroom LED Gridlight, Body made of die cast Aluminium and Frame made of powder coated CRCA and high precision glass lens.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm) L   W   H | MRP (INR) |
|---------------------------|----------|------------|--------------------------|-----------|
| CR2081RFXXN030N00000FL00T | 30       | 120        | 572   572                | 31000     |
| CR2081RFXXN040N00000FL00T | 40       | 120        | 572   572                | 31500     |
| CR2081RFXXN050N00000FL00T | 50       | 120        | 572   572                | 32000     |



## FLAME PROOF CLEANROOM -2X2 PC CR2081

Arraystorm EPIC Flame Proof Recessed High Efficiency Cleanroom LED Gridlight, Body made of die cast Aluminium and Frame made of powder coated CRCA and high precision glass lens.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|----------------------|-----------------------------|-----------|
| CR2081RFXXN060N00000FLOOT | 60       | 120        | 572   572            | 612   612   140             | 44000     |
| CR2081RFXXN080N00000FLOOT | 80       | 120        | 572   572            | 612   612   140             | 44000     |
| CR2081RFXXN100N00000FLOOT | 100      | 120        | 572   572            | 612   612   140             | 45000     |



## FLAME PROOF CLEANROOM -2X2 SS CR2081

Arraystorm EPIC Flame Proof Recessed High Efficiency Cleanroom LED Gridlight, Body made of die cast Aluminium and Frame made of SS and high precision glass lens.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE               | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|----------------------------|----------|------------|----------------------|-----------------------------|-----------|
| CR2081RFXXN030N0000SSFL01T | 30       | 120        | 572   572            | 612   612   140             | 31000     |
| CR2081RFXXN040N0000SSF00T  | 40       | 120        | 572   572            | 612   612   140             | 31000     |
| CR2081RFXXN050N0000SSFL00T | 50       | 120        | 572   572            | 612   612   140             | 31500     |



## FLAME PROOF CLEANROOM -2X2 SS CR2081

Arraystorm EPIC Flame Proof Recessed High Efficiency Cleanroom LED Gridlight, Body made of die cast Aluminium and Frame made of powder coated CRCA and high precision glass lens.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|----------------------|-----------------------------|-----------|
| CR2081RFXXN060N00000FLSST | 60       | 120        | 572   572            | 612   612   140             | 43000     |
| CR2081RFXXN080N00000FLSST | 80       | 120        | 572   572            | 612   612   140             | 44000     |
| CR2081RFXXN100N00000FLSST | 100      | 120        | 572   572            | 612   612   140             | 44500     |

IP65



## FLAME PROOF CLEANROOM -1X2 PC CR2082

Arraystorm EPIC Flame Proof Recessed High Efficiency Cleanroom LED Gridlight, Body made of die cast Aluminium and Frame made of powder coated CRCA and high precision glass lens.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|----------------------|-----------------------------|-----------|
| CR2082RFXXN030N00000FLOOT | 30       | 120        | 275   572            | 312   612   140             | 24000     |
| CR2082RFXXN040N00000FLOOT | 40       | 120        | 275   572            | 312   612   140             | 24750     |
| CR2082RFXXN050N00000FLOOT | 50       | 120        | 275   572            | 312   612   140             | 24750     |

IP65




## FLAME PROOF CLEANROOM -1X2 PC CR2082

Arraystorm EPIC Flame Proof Recessed High Efficiency Cleanroom LED Gridlight, Body made of die cast Aluminium and Frame made of powder coated CRCA and high precision glass lens.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|----------------------|-----------------------------|-----------|
| CR2082RFXXN060N00000FLOOT | 60       | 120        | 275   572            | 312   612   140             | 37500     |
| CR2082RFXXN080N00000FLOOT | 80       | 120        | 275   572            | 312   612   140             | 37500     |
| CR2082RFXXN100N00000FLOOT | 100      | 120        | 275   572            | 312   612   140             | 38000     |

IP65




## FLAME PROOF CLEANROOM -1X2 SS CR2082

Arraystorm EPIC Flame Proof Recessed High Efficiency Cleanroom LED Gridlight, Body made of die cast Aluminium and Frame made of SS and high precision glass lens.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog.

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|----------------------|-----------------------------|-----------|
| CR2082RFXXN030N000SSFLOOT | 30       | 120        | 275   572            | 312   612   140             | 24500     |
| CR2082RFXXN040N000SSFLOOT | 40       | 120        | 275   572            | 312   612   140             | 24750     |
| CR2082RFXXN050N000SSFLOOT | 50       | 120        | 275   572            | 312   612   140             | 25000     |

IP65



## FLAME PROOF CLEANROOM -1X2 SS CR2082

Arraystorm EPIC Flame Proof Recessed High Efficiency Cleanroom LED Gridlight, Body made of die cast Aluminium and Frame made of SS and high precision glass lens.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|----------------------|-----------------------------|-----------|
| CR2082RFXXN060N000SSFLOOT | 60       | 120        | 275   572            | 312   612   140             | 36750     |
| CR2082RFXXN080N000SSFLOOT | 80       | 120        | 275   572            | 312   612   140             | 36750     |
| CR2082RFXXN100N000SSFLOOT | 100      | 120        | 275   572            | 312   612   140             | 37500     |

IP65



## BAYSTAR 2 WG1916 | WG1917 (FLAME PROOF WELL GLASS)

Arraystorm BAYSTAR , Hi-efficiency LED Flame proof Wellglass Luminaire, Body made of di-cast aluminium housing.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>W   H | MRP (INR) |
|---------------------------|----------|------------|-------------------------|-----------|
| WG1916PFXXN030N00002FLOOT | 30       | 120        | 195   155               | 11750     |
| WG1916PFXXN040N00002FLOOT | 40       | 120        | 195   155               | 12500     |
| WG1916PFXXN050N00002FLOOT | 50       | 120        | 195   155               | 12750     |
| WG1917PFXXN060N00002FLOOT | 60       | 120        | 410   155               | 16750     |

IP65



## FLOODSTORM 1 FL0751 (FLAME PROOF FLOODLIGHT)

Arraystorm Floodstorm , Hi-efficiency LED Flame proof Floodlight Luminaire, Body made of di-cast aluminium housing.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|-----------------------------|-----------|
| FL0751PMXXN060N00002FL65T | 60       | 90         | 450   234   132             | 28750     |
| FL0751PMXXN080N00002FL65T | 80       | 90         | 450   234   132             | 29250     |
| FL0751PMXXN100N00002FL65T | 100      | 90         | 450   234   132             | 30000     |

IP65



## FLOODSTORM 2 FL0752 (FLAME PROOF FLOODLIGHT)

Arraystorm Floodstorm , Hi-efficiency LED Flame proof Floodlight Luminaire, Body made of di-cast aluminium housing.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|-----------------------------|-----------|
| FL0752PMXXN120N00002FL65T | 120      | 90         | 664   234   132             | 41500     |
| FL0752PMXXN150N00002FL65T | 150      | 90         | 664   234   132             | 46500     |

IP65



## FLOODSTORM 3 FL0753 (FLAME PROOF FLOODLIGHT)

Arraystorm Floodstorm , Hi-efficiency LED Flame proof Floodlight Luminaire, Body made of di-cast aluminium housing.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>W   H | MRP (INR) |
|---------------------------|----------|------------|-------------------------|-----------|
| FL0753PMXXN160N00002FL65T | 160      | 90         | 450   450   132         | 50250     |
| FL0753PMXXN200N00000FL65T | 200      | 90         | 450   450   132         | 54000     |

IP65



## FLAMEPROOF OPTIMUS STREETLIGHT 1

Arraystorm OPTIMUS 2 Flame Proof LED Streetlight, Body made of di-cast aluminium housing.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|-----------------------------|-----------|
| ST0851PFXXN030N00002FLOOT | 30       | 90         | 455   240   185             | 15500     |
| ST0851PFXXN040N00002FLOOT | 40       | 90         | 455   240   185             | 15750     |
| ST0851PFXXN050N00002FLOOT | 50       | 90         | 455   240   185             | 16000     |
| ST0852PFXXN060N00002FLOOT | 60       | 90         | 455   240   185             | 27750     |
| ST0852PFXXN080N00002FLOOT | 80       | 90         | 455   240   185             | 28750     |
| ST0852PFXXN100N00002FLOOT | 100      | 90         | 455   240   185             | 30250     |

IP65



## REACTOR - FLAME PROOF RL0922

Arraystorm BAYSTAR 2 , Hi-efficiency LED Flame proof Reactor Luminaire, Body made of di-cast aluminium housing.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>W   H | MRP (INR) |
|---------------------------|----------|------------|-------------------------|-----------|
| RL0922PFXXN010N00002FLOOT | 10       | 120        | 156   276               | 8750      |
| RL0922PFXXN020N00002FLOOT | 20       | 120        | 156   276               | 9250      |
| RL0922PFXXN040N00002FLOOT | 40       | 120        | 156   276               | 10500     |

IP65



## LINEAR FLAMEPROOF CL1271

Arraystorm BAYSTAR , Hi-efficiency LED Flame proof LinearLight, Body made of extruded aluminium housing.

230 V with standard driver, CRI>80,  
CCT available in 3000K/4000K/5700K.  
Driver also available in DALI | Analog

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|-----------------------------|-----------|
| CL1271PFXXN030N2FS02FLOOT | 30       | 120        | 127   105   500             | 16750     |
| CL1271PFXXN040N2FS02FLOOT | 40       | 120        | 127   105   500             | 17000     |
| CL1271PFXXN050N2FS02FLOOT | 50       | 120        | 127   105   500             | 17500     |
| CL1271PFXXN030N4FS02FLOOT | 30       | 120        | 127   105   1000            | 29000     |
| CL1271PFXXN040N4FS02FLOOT | 40       | 120        | 127   105   1000            | 31000     |
| CL1271PFXXN050N4FS02FLOOT | 50       | 120        | 127   105   1000            | 31000     |





# LANDSCAPE



## ARRAYSTORM LED BOLLARD LIGHT BO6101

Arraystorm BOLLARD BO6102 , Hi-efficiency LED Bollard Light, Body made of extruded aluminium housing, die cast heat Sink and Translucent Diffuser.

230 V with standard driver, CRI>80,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | DIMENSION (mm)<br>W   H | MRP (INR) |
|---------------------------|----------|-------------------------|-----------|
| BO6101PF30N010N600020065T | 10       | 70   600                | 5500      |



## ARRAYSTORM LED BOLLARD LIGHT BO6102

Arraystorm BOLLARD BO6102 , Hi-efficiency LED Bollard Light, Body made of extruded aluminium housing, die cast heat Sink and Translucent Diffuser.

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | DIMENSION (mm)<br>W   H | MRP (INR) |
|---------------------------|----------|-------------------------|-----------|
| BO6102PF30N010N600020065T | 10       | 100   600               | 5750      |



## ARRAYSTORM LED BOLLARD LIGHT BO6103

Arraystorm BOLLARD BO6103 , Hi-efficiency LED Bollard Light, Body made of extruded aluminium housing, Spun Aluminium top Cover and Polycarbonate Frosted Diffuser.

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | DIMENSION (mm)<br>W   H | MRP (INR) |
|---------------------------|----------|-------------------------|-----------|
| BO6103PF30N012N600020065T | 12       | 250   600               | 7750      |



## ARRAYSTORM LED BOLLARD LIGHT BO6104

Arraystorm BOLLARD BO6104 , Hi-efficiency LED Bollard Light, Body made of extruded aluminium housing, die cast heat Sink and Clear Polycarbonate Diffuser.

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | DIMENSION (mm)<br>W   H | MRP (INR) |
|---------------------------|----------|-------------------------|-----------|
| BO6104PF30N010N600020065T | 10       | 100   600               | 8500      |



## ARRAYSTORM LED BOLLARD LIGHT BO6105

Arraystorm BOLLARD BO6105 , Hi-efficiency LED Bollard Light, Body made of extruded aluminium housing, die cast heat Sink and Opal Polycarbonate Diffuser.

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | DIMENSION (mm)<br>W   H | MRP (INR) |
|---------------------------|----------|-------------------------|-----------|
| BO6105PF30N012N600020065T | 12       | 105   600               | 9000      |



## ARRAYSTORM LED BOLLARD LIGHT BO6106

Arraystorm BOLLARD BO6106 , Hi-efficiency LED Bollard Light, Body made of extruded aluminium housing, die cast heat Sink and clear Polycarbonate Diffuser.

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|-----------------------------|-----------|
| BO6106PF30N015N600020065T | 15       | 120   120   120             | 9500      |



## ARRAYSTORM LED BOLLARD LIGHT BO6107

Arraystorm BOLLARD BO6107 , Hi-efficiency LED Bollard Light, Body made of extruded aluminium housing, die cast aluminium Top Cover, and clear Polycarbonate Diffuser Diffuser.

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|-----------------------------|-----------|
| BO6107PF30N010N600020065T | 10       | 130   130   130             | 9500      |



## ARRAYSTORM LED BOLLARD LIGHT BO6108

Arraystorm BOLLARD BO6108 , Hi-efficiency LED Bollard Light, Body made of extruded aluminium housing, die cast aluminium Top Cover, and clear Polycarbonate Diffuser Diffuser.

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|-----------------------------|-----------|
| BO6108PF30N010N600020065T | 10       | 100   100   600             | 9500      |



## ARRAYSTORM LED BOLLARD LIGHT BO6109

Arraystorm BOLLARD BO6108 , Hi-efficiency LED Bollard Light, Body made of extruded aluminium housing, die cast aluminium Top Cover, and Opal Diffuser Diffuser.

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|-----------------------------|-----------|
| BO6109PF30N012N450020065T | 12       | 225   50   450              | 7000      |
| BO6109PF30N012N600020065T | 12       | 225   50   600              | 8250      |
| BO6109PF30N012N900020065T | 12       | 225   50   900              | 10000     |



## ARRAYSTORM LED POST TOP LIGHT PT6063

Arraystorm LED Post Top Light PT6063 , Hi-efficiency LED Bollard Light, Body made of extruded aluminium housing, die cast aluminium Top Cover, and clear Polycarbonate Diffuser.

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|-----------------------------|-----------|
| PT6063PF30N013N000020065T | 13       | 150   150   200             | 8000      |



## ARRAYSTORM LED POST TOP LIGHT PT6061

Arraystorm POST TOP PT6061 , Hi-efficiency LED Post Top Light, with die cast Aluminium Base, Spun aluminium Top Cover and Polycarbonate clear Diffuser.

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|-----------------------------|-----------|
| PT6061PF30N045N000020065T | 45       | 350   460                   | 10000     |
| PT6061PF30N060N000020065T | 60       | 350   460                   | 13500     |



## ARRAYSTORM LED POST TOP LIGHT PT6062

Hi-efficiency LED Post Top Light, with die cast Aluminium Base, Spun aluminium Top Cover and Opal Diffuser Diffuser.

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|-----------------------------|-----------|
| PT6062PF30N018N000020065T | 18       | 260   430                   | 6250      |
| PT6062PF30N025N000020065T | 25       | 260   430                   | 7250      |



## ARRAYSTORM LED POST TOP LIGHT PT6071/PT6072

Arraystorm POST TOP PT6062/6072 , Hi-efficiency LED Post Top Light, with die cast Aluminium Base, Spun aluminium Top Cover and Opal Diffuser.

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|-----------------------------|-----------|
| PT6071PF30N030N000020065T | 30       | 405   220                   | 19000     |
| PT6071PF30N050N000020065T | 50       | 405   220                   | 26500     |
| PT6072PF30N060N000020065T | 60       | 600   415                   | 34000     |



## ARRAYSTORM LED POST TOP LIGHT PT6073/PT6074

Arraystorm POST TOP LIGHT PT6073/PT6074 , Hi-efficiency LED Post Top Light, with die cast Aluminium Housing and Polycarbonate Opal Diffuser.

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | DIMENSION (mm)<br>W   H | MRP (INR) |
|---------------------------|----------|-------------------------|-----------|
| PT6073PF30N030N000020065T | 30       | 250   255               | 20750     |
| PT6074PF30N060N000020065T | 60       | 440   440               | 35000     |



## ARRAYSTORM LED POST TOP LIGHT PT6075

Arraystorm POST TOP PT6075 , Hi-efficiency LED Post Top Light, with die cast Aluminium Housing and Polycarbonate Opal Diffuser and toughened glass.

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | DIMENSION (mm)<br>W   H | MRP (INR) |
|---------------------------|----------|-------------------------|-----------|
| PT6075PF30N040N000020065T | 40       | 600   850               | 40250     |




## ARRAYSTORM LED POST TOP LIGHT PT6076/PT6077

Arraystorm POST TOP PT6076/PT6077 , Hi-efficiency LED Post Top Light, with die cast Aluminium Housing and Polycarbonate Opal Diffuser.

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|-----------------------------|-----------|
| PT6077PF30N040N000020065T | 40       | 750   40   750              | 37500     |




## ARRAYSTORM LED POST TOP LIGHT PT6078

Arraystorm POST TOP PT6078 , Hi-efficiency LED Post Top Light, with die cast Aluminium Housing, spun aluminium Top Cover and Polycarbonate Clear Diffuser with street-light Lens.

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | DIMENSION (mm)<br>W   H | MRP (INR) |
|---------------------------|----------|-------------------------|-----------|
| PT6078PF30N045N000020065T | 45       | 515   470               | 19000     |
| PT6078PF30N060N000020065T | 60       | 515   470               | 21250     |
| PT6078PF30N072N000020065T | 72       | 515   470               | 22250     |



## ARRAYSTORM LED POST TOP LIGHT PT6079

Arraystorm POST TOP PT6079 , Hi-efficiency LED Post Top Light, with die cast Aluminium Housing, spun aluminium Top Cover and Polycarbonate Clear Diffuser with street-light Lens.

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | DIMENSION (mm)<br>W   H | MRP (INR) |
|---------------------------|----------|-------------------------|-----------|
| PT6079PF30N090N000020065T | 90       | 660   650               | 32000     |
| PT6079PF30N120N000020065T | 120      | 660   650               | 35000     |
| PT6079PF30N150N000020065T | 150      | 660   650               | 35750     |



## ARRAYSTORM LED POST TOP LIGHT PT6080

Arraystorm POST TOP PT6080 , Hi-efficiency LED Post Top Light, with die cast Aluminium Housing and Polycarbonate Opal Diffuser.

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | DIMENSION (mm)<br>W   H | MRP (INR) |
|---------------------------|----------|-------------------------|-----------|
| PT6080PF30N030N000020065T | 30       | 405   220               | 18500     |
| PT6080PF30N050N000020065T | 50       | 405   220               | 26000     |



## ARRAYSTORM LED BUSH LIGHT BL6001

Arraystorm Bush Light BL6001 , Hi-efficiency LED Bush Light, with die cast Aluminium Housing and Toughned Glass.

With Spike 230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|-----------------------------|-----------|
| BL6001SK30N003N000020065T | 3        | 45         | 45   45   45                | 2500      |



## ARRAYSTORM LED BUSH LIGHT BL6003

Arraystorm Bush Light BL6003 , Hi-efficiency LED Bush Light, with die cast Aluminium Housing and Toughned Glass,

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|-----------------------------|-----------|
| BL6002FF30N006N000020065T | 6        | 45         | 65   65   65   235          | 3500      |
| BL6002FF30N009N000020065T | 9        | 45         | 65   65   65   235          | 4000      |
| BL6002FF30N012N000020065T | 12       | 45         | 65   65   65   235          | 4750      |
| BL6003SK30N020N000000065T | 20       | 45         | 120   120   120   210       | 11750     |



## ARRAYSTORM LED BUSH LIGHT BL6004

Arraystorm Bush Light BL6004 , Hi-efficiency LED Bush Light, with die cast Aluminium Housing and Toughned Glass.

With Spike 230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|-----------------------------|-----------|
| BL6004SK30N003N000020065T | 3        | 90         | 70   80   260               | 2250      |



## ARRAYSTORM LED BUSH LIGHT BL6005

Arraystorm Bush Light BL6005 , Hi-efficiency LED Bush Light, with die cast Aluminium Housing and Toughned Glass.

With Spike and Hood 230 V with standard driver, CRI>70, CCT available in 3000K

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|-----------------------------|-----------|
| BL6005SK30N008N000020065T | 8        | 90         | 105   140   350             | 3750      |
| BL6005SK30N012N000020065T | 12       | 90         | 105   140   350             | 4750      |



## ARRAYSTORM LED WALL LIGHT WL6041

Arraystorm Wall Light WL6041 , Hi-efficiency LED Bush Light, with die cast Aluminium Housing and Sharp beam angle len Polycarbonate Lens 230 V with standard driver,

CRI>70, CCT available in 3000K

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|-----------------------------|-----------|
| WL6041WF30N004N000020065T | 1X4      | 10         | 105   105   50              | 3750      |



## ARRAYSTORM LED WALL LIGHT WL6042

Arraystorm Wall Light WL6042 , Hi-efficiency LED Bush Light, with die cast Aluminium Housing and Sharp beam angle len Polycarbonate Lens 230 V with standard driver,

CRI>70, CCT available in 3000K

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|-----------------------------|-----------|
| WL6042WF30N004N000020065T | 1X4      | 60         | 75   75   50                | 3750      |



## ARRAYSTORM LED WALL LIGHT WL6043

Arraystorm Wall Light WL6043 , Hi-efficiency LED Bush Light, with die cast Aluminium Housing and Toughned glass

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|-----------------------------|-----------|
| WL6043WF30N005N000020065T | 5        | 80         | 80   65   75                | 2500      |



## ARRAYSTORM LED UP DOWN WALL LIGHT WL6044

Arraystorm UP-Down Wall Light WL6044 , Hi-efficiency LED Bush Light, with die cast Aluminium Housing and Toughned glass

230 V with standard driver, CRI>70,  
CCT available in 3000K/

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|-----------------------------|-----------|
| WL6044UD30N005N000020565T | 2X5      | 80         | 80   65   140               | 3000      |



## ARRAYSTORM LED UP-DOWN WALL LIGHT BL6047/6048

Arraystorm UP Down Wall Light BL6047/6048 , Hi-efficiency LED Bush Light, with die cast Aluminium Housing and Toughned glass

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|-----------------------------|-----------|
| WL6047WF30N006N122020065T | 2x6      | 80         | 60   80   122               | 5000      |
| WL6048WF30N009N190020965T | 2X9      | 80         | 80   115   190              | 9500      |



## ARRAYSTORM LED UP-DOWN WALL LIGHT BL6049/6050

Arraystorm UP Down Wall Light BL6049/6050 , Hi-efficiency LED Bush Light, with die cast Aluminium Housing and Toughened glass

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|-----------------------------|-----------|
| WL6049WF30N006N160020065T | 1X6      | 45         | 75   105   160              | 6750      |
| WL6050UD30N006N190020665T | 2X6      | 45         | 75   105   235              | 9750      |



## ARRAYSTORM STEP LIGHT SP6031

Arraystorm Step Light SP6031 , Hi-efficiency LED Recess mounted Step Light, with die cast Aluminium Housing and Prismatic Opal Diffuser

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>W   H | MRP (INR) |
|---------------------------|----------|------------|----------------------|-------------------------|-----------|
| SP6031RF30N003N000020065T | 3        | 110        | 80   80              | 90   90   80            | 1650      |



## ARRAYSTORM LED RECESS MOUNTED STEP LIGHT SP6032

Arraystorm Step Light SP6032 , Hi-efficiency LED Recess mounted Step Light, with die cast Aluminium LED Recess mounted Housing and Prismatic Opal Diffuser

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | CUTOUT (mm)<br>L   W | DIMENSION (mm)<br>W   H | MRP (INR) |
|---------------------------|----------|------------|----------------------|-------------------------|-----------|
| SP6032RF30N006N000020065T | 6        | 110        | 115   75             | 125   85   50           | 3000      |
| SP6033RF30N009N000020065T | 9        | 110        | 125   80             | 135   90   50           | 3500      |



## ARRAYSTORM LED SURFACE MOUNTED STEP LIGHT SP6131/SP6132

Arraystorm Step Light SP6031 / SP6132 , Hi-efficiency LED Surface mounted Step Light, with die cast Aluminium Housing and Prismatic Opal Diffuser 230 V with standard

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm)<br>L   W   H | MRP (INR) |
|---------------------------|----------|------------|-----------------------------|-----------|
| SP6131FF30N003N000020065T | 3        | 110        | 90   60   40                | 2000      |
| SP6132FF30N008N000020065T | 8        | 110        | 150   70   40               | 2750      |



## ARRAYSTORM LED SURFACE MOUNTED DOWN LIGHT WL6041

Arraystorm Down Light WL6041 , Hi-efficiency LED Surface mounted Wall Light, with die cast Aluminium Housing and Prismatic Opal Diffuser

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm) W   H | MRP (INR) |
|---------------------------|----------|------------|----------------------|-----------|
| WL6041WFXXN018N000000054T | 18       | 120        | 210   60             | 4250      |



## ARRAYSTORM LED SURFACE MOUNTED METEOR 1 SPOT LIGHT SL3202

Arraystorm Wall Light SL3202 , Hi-efficiency LED Bush Light, with die cast Aluminium Housing and Toughned glass

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm) L   W   H | MRP (INR) |
|---------------------------|----------|------------|--------------------------|-----------|
| SL3202FF30N008N000020065T | 8        | 36         | 90   90   140            | 8000      |



## ARRAYSTORM LED SURFACE WALL WASHER LIGHT MOUNTED STEP LIGHT WW6021

Arraystorm Wall Washer Light WW6021 , Hi-efficiency LED , with High Aluminium Extruded Housing and Toughned glass

230 V with standard driver, CRI>70,  
CCT available in 3000K

| PRODUCT CODE              | WATT (W) | BEAM ANGLE | DIMENSION (mm) L   W   H | MRP (INR) |
|---------------------------|----------|------------|--------------------------|-----------|
| WW6021WMXXN018N500020065T | 18       | 36         | 45   65   500            | 13500     |
| WW6021WMXXN036N1MT020065T | 36       | 36         | 45   65   1000           | 19000     |





A modern interior space, possibly a lounge or office, with large windows, contemporary furniture, and two pendant lights. The image is overlaid with large, diagonal orange geometric shapes. A white rectangular box with an orange border is centered in the middle of the image.

# LIGHTING CONTROLS



## WIRED PIR 16A SENSOR (RECESS)

Presence Detector PIR Light controlling Sensors help to reduce energy consumption by automatically turning off lights when no one is around. The application of these are for office, school, hospital, retail, and other commercial applications. These are commonly used in stairways and passages, Manager and Conference rooms.

| PRODUCT CODE              | Description                                     | MRP (INR) |
|---------------------------|-------------------------------------------------|-----------|
| SE6303RFSTX016XPIRXX0000T | PIR Recess Mounted 6 A Stand alone wired sensor | 4000      |



## WIRED PIR 16A SENSOR (SURFACE)

Presence Detector PIR Light controlling Sensors help to reduce energy consumption by automatically turning off lights when no one is around. The application of these are for office, school, hospital, retail, and other commercial applications. These are commonly used in stairways and passages, Manager and Conference rooms.

| PRODUCT CODE              | Description                                      | MRP (INR) |
|---------------------------|--------------------------------------------------|-----------|
| SE6304FFSTX016XPIRXX0000T | PIR Surface Mounted 6 A Stand alone wired sensor | 6000      |



## LIGHT INTEGRATED PIR 6A SENSOR (RECESS)

Presence Detector PIR Light controlling Sensors help to reduce energy consumption by automatically turning off lights when no one is around. The application of these are for office, school, hospital, retail, and other commercial applications. These are commonly used in stairways and passages, Manager and Conference rooms.

| PRODUCT CODE              | Description                                       | MRP (INR) |
|---------------------------|---------------------------------------------------|-----------|
| SE6305RFLIX016XPIRXX0000T | PIR Light Integrated 6 A Stand alone wired sensor | 3000      |



## IOT LIGHT INTEGRATED PIR SENSOR

Presence Detector IoT PIR Light Integrated controlling Sensors help to reduce energy consumption by automatically turning off lights when no one is around. These also send information two way between the Sensors/ IoT Drivers and the centralised gateway through Wireless RF Transmission and receive information from it. The application of these are for office, school, hospital, retail, and other commercial applications. These are commonly used in stairways and passages, Manager and Conference rooms. To be used along with the Arraystorm IoT Load Controller or IoT Driver

| PRODUCT CODE              | Description                     | MRP (INR) |
|---------------------------|---------------------------------|-----------|
| SE6321RFLIW006XPIRXX0000T | PIR Light Integrated IoT sensor | 3000      |



## IOT LIGHT INTEGRATED PIR+DAYLIGHT SENSOR

Presence Detector IoT PIR+ Daylight Light Integrated Sensors help to reduce energy consumption by automatically turning off lights when no one is around or Dim the Lights based on Lux settings. These also send information two way between the Sensors/ IoT Drivers and the centralised gateway through Wireless RF Transmission and receive information from it. The application of these are for office, school, hospital, retail, and other commercial applications. These are commonly used in stairways and passages, Manager and Conference rooms.

| PRODUCT CODE              | Description                                | MRP (INR) |
|---------------------------|--------------------------------------------|-----------|
| SE6322RFLIW006XPIRDL0000T | PIR + Daylight Light Integrated IoT sensor | 3750      |



## IOT STANDALONE RECESS MOUNTED PIR SENSOR

Presence Detector IoT PIR Stand aloneLight Sensors help to reduce energy consumption by automatically turning off lights when no one is around. These also send information two way between the Sensors/ IoT Drivers and the centralised gateway through Wireless RF Transmission and receive information from it. The application of these are for office, school, hospital, retail, and other commercial applications. These are commonly used in stairways and passages, Manager and Conference rooms.

| PRODUCT CODE              | Description                               | MRP (INR) |
|---------------------------|-------------------------------------------|-----------|
| SE6323RFSTW006XPIRXX0000T | PIR Stand Alone Recess Mounted IoT sensor | 13500     |



## IOT STANDALONE RECESS MOUNTED PIR + DAYLIGHTSENSOR

Presence Detector IoT PIR+ Daylight Stand alone Light Sensors help to reduce energy consumption by automatically turning off lights when no one is around or Dim the Lights based on Lux settings. These also send information two way between the Sensors/ IoT Drivers and the centralised gateway through Wireless RF Transmission and receive information from it. The application of these are for office, school, hospital, retail, and other commercial applications. These are commonly used in stairways and passages, Manager and Conference rooms.

| PRODUCT CODE              | Description                                          | MRP (INR) |
|---------------------------|------------------------------------------------------|-----------|
| SE6323RFSTW006XPIRDL0000T | PIR + Daylight Stand Alone Recess Mounted IoT sensor | 14000     |



## IOT STANDALONE SURFACE MOUNTED PIR SENSOR

Presence Detector IoT PIR Stand alone Light Sensors help to reduce energy consumption by automatically turning off lights when no one is around. These also send information two way between the Sensors/ IoT Drivers and the centralised gateway through Wireless RF Transmission and receive information from it. The application of these are for office, school, hospital, retail, and other commercial applications. These are commonly used in stairways and passages, Manager and Conference rooms.

| PRODUCT CODE              | Description                                | MRP (INR) |
|---------------------------|--------------------------------------------|-----------|
| SE6324FFSTW006XPIRXX0000T | PIR Stand Alone Surface Mounted IoT sensor | 13500     |



## IOT STANDALONE SURFACE MOUNTED PIR + DAYLIUGHT SENSOR

Presence Detector IoT PIR+ Daylight Stand alone Light Sensors help to reduce energy consumption by automatically turning off lights when no one is around or Dim the Lights based on Lux settings. These also send information two way between the Sensors/ IoT Drivers and the centralised gateway through Wireless RF Transmission and receive information from it. The application of these are for office, school, hospital, retail, and other commercial applications. These are commonly used in stairways and passages, Manager and Conference rooms.

| PRODUCT CODE              | Description                                           | MRP (INR) |
|---------------------------|-------------------------------------------------------|-----------|
| SE6324FFSTW006XPIRDL0000T | PIR + Daylight Stand Alone Surface Mounted IoT sensor | 14000     |



## IOT LIGHT INTEGRATED IR BLASTER FOR AC

IoT IR Blaster helps to reduce energy consumption by automatically turning off Stand alone Split AC's when no one is around based on information received from the presence IoT PIR sensors. These also send information two way between the Sensors/ IoT Drivers and the centralised gateway through Wireless RF Transmission and receive information from it. The application of these are for office, school, hospital, retail, and other commercial applications. These are commonly used in stairways and passages, Manager and Conference rooms.

| PRODUCT CODE              | Description                            | MRP (INR) |
|---------------------------|----------------------------------------|-----------|
| SE6325FFSTW000XIRBXX0000T | IoT Light Integrated IR Blaster for AC | 15000     |



## IOT GATEWAY

IoT Gateway to be used along with the IoT Presence detector, IoT Drivers, IoT Loads and IoT system and send a two way information to other IoT devices and the main gateway and to the Software and receive instruction centrally. The application of these are for office, school, hospital, retail, and other commercial applications. These are commonly used in stairways and passages, Manager and Conference rooms.

| PRODUCT CODE | Description | MRP (INR) |
|--------------|-------------|-----------|
| 115050000000 | IoT Gateway | 84000     |



## IOT LOAD CONTROLLER 6A

Arraystorm Wireless Communication IoT Load Controller 6A, used to control the Power to the Light fixture Driver to Switch on-Off and to be used along with the Arraystorm IoT Sensor. The application of these are for office, school, hospital, retail, and other commercial applications. These are commonly used in stairways and passages, Manager and Conference rooms.

| PRODUCT CODE | Description            | MRP (INR) |
|--------------|------------------------|-----------|
| 112536030000 | IoT Load Controller 6A | 7250      |



## MULTI PURPOSE REMOTE (RF)

Remote Multi purpose WH T100R-V5 can control light which has RF Drivers installed inside the Luminaire. Switch off/ Color Change/ Dimming can be controlled.

| PRODUCT CODE | Description             | MRP (INR) |
|--------------|-------------------------|-----------|
| 115040000000 | Multi Purpose Remote RF | 1750      |



## BLUETOOTH IOT GATEWAY

Arraystorm RF+BT controller Gateway can control 100 groups of lamps.4Step\ - Stepless dimming and color- 146\*45.5\*17.5mm temp adjusting, Individual\groups control, Scene Preset/Recall, Night Light Mode, Remote ID.

| PRODUCT CODE | Description           | MRP (INR) |
|--------------|-----------------------|-----------|
| 115050000000 | Bluetooth IoT Gateway | 8750      |



## SCENE SWITCH 6 KEYS

Arraystorm Scene Switch 6 Keys, ON/OFF, 4 Scenes Recall, Dimming and CCT Adjusting, Wireless- (Switch Scene Controller) Powered by Battery CR2330. Available in White and Dark Grey Colour.

| PRODUCT CODE | Description         | MRP (INR) |
|--------------|---------------------|-----------|
| 115030000000 | Scene switch 6 keys | 5500      |



# General conditions of business

---

- All prices are in Indian Rupees only
- List price are inclusive of GST. However authorized Arraystorm Sales teams / channel partners and Stockists can sell below the List price
- All prices are subject to RR Kabel's general terms and condition of business
- All prices are with standard product specifications. Any changes in understanding of specifications would lead to a price difference
- Prices lists are subject to change without notice as per company's discretion
- Company reserves the right to issue amendments, which may rise due to any errors in price list
- Continuous design changes is a routine practice of RR Kabel. Data provided may change without any prior intimation
- Customers are advised to reconfirm the data or product dimensions before purchase with our local offices
- All orders should be placed in writing
- All orders should be placed in the name of RR Kabel Limited. Arraystorm is a lighting brand owned by RR Kabel Ltd
- All orders to be placed in multiples of case lots only
- Disputes, if any are subject to Mumbai jurisdiction
- This price list supersedes any prior price list of Arraystorm.

---

Although every effort has been made to ensure accuracy in the compilation of the technical detail in this price list, however the current details' specifications of all components needs to be checked with RR Kabel's Arraystorm team before placing of orders as the Specifications , design and the performance data are constantly being upgraded till the issue of next price list.

**Copyright notice:** Imitation of product images, Trademark's, graphics and color scheme of this document is a Punishable offence.

# RR KABEL LIMITED

---

**H.O Arraystorm Lighting Div.:**No. 2318 , 2nd Floor,  
Sector 1, HSR Layout, Bangalore – 560 102, Karnataka, INDIA  
T: +91-80-2655-111 || E : info.arraystorm@rrglobal.com

**Factory :** Plot no 9-O sub layout of Yarandahalli,  
Bommasandra Industrial Area 1st Phase, Jigni Hobli,  
Taluk, Anekal, Karnataka 560099 Karnataka, INDIA

## South

---

### Bangalore

2318, 2nd Floor, 27th Main Road,  
Hsr Layout Sector 1, Bangalore - 560102

### Chennai

248, G2, Prince Centre, Pathari Rd, Thousand Lights East,  
Thousand Lights, Chennai, Tamil Nadu 600006

### Hyderabad

Hyderabad: Unit No: 1103, 11th Floor Commercial Block, T  
19 Tower Karbala Maidan, Ranigunj, Secunderabad,  
Telangana - 500003

### Coimbatore

Site No. 34, First Floor, Hindustan Avenue  
Hindustan College Road Nava india.  
City: Coimbatore, Pin: 641028, State: Tamil Nadu

## North

---

### NCR

401,4th Floor, Global Business Square,Building no 32, Sector  
44,Gurugram-122003

### Lucknow

tM-6, Indralok Colony, Krishna Nagar, Alambagh, Opp.  
Shesarveer Mandir, Lucknow - 226 023

## West

---

### Mumbai

10th Floor, RCity Mall, LBS Marg, Building,  
Ghatkopar (West) Mumbai 400086

### Pune

RR KABEL LIMITED 1st Floor, 105/1/1/4, Carax Building,  
Opp Sadanand Resorts, Baner, Pune – 411 045

### Ahmedabad

B-801,8th Floor,Mondeal Heights,  
Beside Hotel Novotel, S.G. Highway,  
Opposite Karnavati Club, City: Ahmedabad, Pin: 380015

### Baroda

Alembic Business Park (West) Ground Floor,  
Bhailal Amin Marg Gorwa, Vadodara - 390003  
City: Vadodara, Pin: 39003

### Surat

Hg-13, Higher Ground Floor  
International Trade Centre Majura Gate.  
City: Surat, Pin: 395002, State: Gujaratt



---

Ram Ratna House, Oasis Complex, P.B Marg, Worli, Mumbai - 400 013.

T:+91 -22-2494 9009 / 2492 4144 F: +91 - 22 - 2491 2586 E: [mumbai.rrkabel@rrglobal.com](mailto:mumbai.rrkabel@rrglobal.com)

Alembic Business Park (West) Ground Floor, Bhailal Amin Marg Gorwa, Vadodara – 390003 City: Vadodara,

T- +91-265-6830 800 email: [vadodara.rrkabel@rrglobal.com](mailto:vadodara.rrkabel@rrglobal.com)

## RR KABEL LIMITED

---

**Regd. Office :** Ram Ratna House, Oasis Complex, P.B. Marg, Worli, Mumbai - 400 013

**H.O Arraystorm Lighting Div.:**No. 2318 , 2nd Floor, Sector 1, HSR Layout, Bangalore – 560 102, Karnataka, INDIA

**Factory :** Plot no 9-O sub layout of Yarandahalli, Bommasandra Industrial Area 1st Phase, Jigni Hobli, Taluk, Anekal, Karnataka 560099 Karnataka, INDIA T: +91-80-2655-111 E : [info@rrglobal.com](mailto:info@rrglobal.com)